

2340M, 2540M, 2540MK Manual Sterilizers

Tuttnauer manual autoclaves will compliment any healthcare facility and satisfy all of your sterilization needs. The bright, new, easy to use panel was designed with the operator in mind. Time tested reliability and durability are built into every Tuttnauer product.



Features:

- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished Stainless Steel chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.
- 1 year parts and labor warranty. 10 year chamber warranty



- 1 Pressure Gauge
- 2 Timer
- 3 Thermostat
- 4 Function Selector

M - Manual Series

Item No.	Chamber Dimensions Ø x L in(mm)	Vol	Overall Dimensions DxWxH in(mm)	Standard Cassette Capacity**	Tray Dimensions DxWxH in(mm)	No. of Trays	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz)	Power(W) Current(A)	Shipping Weight lbs(kg)
2340M	9" x 18" (230 x 470)	5gal/ 19L	21.5"x20"x14.4" (545x510x365)	2 full & 2 half	16.3"x 6.7"x0.8" (415x170x20)	3	Cold: 27 mins Hot: 13 mins	120V 50/60	1400W 12A	84 (38)
2540M	10" x 19" (254 x 475)	6gal/ 23L	21.5"x20"x14.4" (545x510x365)	3 full & 3 half	16.3"x 6.7"x0.8" (415x170x20)	4	Cold: 30 mins Hot: 14 mins	120V 50/60	1400W 12A	84 (38)

MK - Manual Kwiklave™ Series

2540MK	10" x 19" (254 x 475)	6gal/ 23L	21.5"x20"x14.4" (545x510x365)	3 full & 3 half	16.3"x 6.7"x0.8" (415x170x20)	4	Cold: 21 min Hot: 11 min	230V 50/60*	2200W 10A	84 (38)
--------	--------------------------	--------------	----------------------------------	--------------------	----------------------------------	---	-----------------------------	----------------	--------------	------------

NOTE: cycle times are approximate and may vary depending on instrument loads. **Standard full size cassette is 8" x 11" and standard half size cassette is 8" x 5.5".

The Tuttnauer M Series is also available in a quick cycle model, the Kwiklave (MK). This sterilizer offers all the proven, dependable features of our manual autoclave, with the added benefit of reducing the total heat up time. This autoclave is the perfect choice for quick instrument turnaround or a high volume office. Speed and reliability are accomplished without sacrificing load size. 1 year parts and labor warranty.

Model 2540MK requires a voltage between 220V and 235V for proper operation. When applicable a buck/boost transformer (0.5KVA) may be required*

