



**Tuttnauer**  
Innovation · Legacy · Partnership

LEADING IN  
STERILIZATION  
SINCE  
**1925**

# T-Top 10 Autoclave

- ◆ Low Cost - Top Performance
- ◆ Class S Sterilizer (Closed-Door Drying)
- ◆ T-Connect: Advanced Remote Diagnostics
- ◆ Short Cycles
- ◆ Large Chamber Capacity
- ◆ Clean water with every cycle!  
Separate water reservoirs for clean/used water



P/N: T-Top 10S 110V



## Plug and Play

**No dedicated installation connections required**

- ◆ Multicolour user-friendly touch screen with intuitive icons
- ◆ Easy - just start and run programs
- ◆ Compact and ergonomic, designed to fit into your space



## Traceability & Connectivity

**Advanced Technology that provides real-time data intelligence**

- ◆ 2 USB Ports
- ◆ Wi-Fi connection & T-Connect software
- ◆ Remotely access cycle history, get notifications and alerts.
- ◆ Paperless documentation



## Reliable Performance

**Quality product that will do all you need and expect**

- ◆ Easy to operate, maintain and use
- ◆ Internal memory - storing up to 500 cycles
- ◆ Advanced technology to deliver



## Innovation

**Best in class technology**

- ◆ Programming and customization functions
- ◆ Specially designed user interface to speed up and optimize daily workload
- ◆ Time saver setting to set tests and sterilization cycles to start at any time








## Cloud based paperless software

T-Top devices feature the exclusive and technologically advanced T-Connect, a cloud based IoT solution for your sterilization center.



# T-Top Sterilization Cycle Programs

Icon	Program name	Sterilization Times (w/ Drying)*	Load Type	Type of Use
	Unwrapped 273°F	25 min	Unwrapped Instruments	For immediate use
	Wrapped 273°F	56 min	Wrapped Pouches	For storage
	Unwrapped 250°F	46 min	Unwrapped Delicate Instruments	For immediate use
	Wrapped 250°F	72 min	Wrapped Delicate Instruments	For storage
	Wrapped 250°F / 2 Kg	42 min	Small Loads of up to 4.4 lbs.	For quick turnaround of small loads

\* Cycle times above are an average for a standard load and could vary based on load weight, type, and external conditions

## T-Top Technical Specifications



Chamber size	10 (W) x 18 (D)
Volume	21L
Overall dimensions	23" (D) x 18.1" (W) x 18" (H)
Max # of trays	5 (sold with 4 trays, additional available for purchased)
Tray dimensions	14.7" (D) x 7.3" (W) x 0.6" (H)
Weight	99 lbs.
Water filling	manual

### Tuttnauer USA Co.

345 Oser Ave.  
Hauppauge, NY 11788  
Tel: +800 624 5836, +631 737 4850  
Fax: +631 737 0720  
E-mail: [info@tuttnauerUSA.com](mailto:info@tuttnauerUSA.com)



[dhpsupply.com](http://dhpsupply.com) | 800.626.2163

