

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Plus_-Fluorescence_-Solar

Revision date: 13.04.2016 Product code: 110368, 110400-110404, 110406, 110-585-110589, 110710, 110719, 110722, 110723, 110360 (1300-GHS)

Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Luxatemp Plus_-Fluorescence_-Solar

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

| | | |
|---------------|-----------------------|-------------------------|
| Company name: | DMG America LLC | |
| Street: | 242 South Dean Street | |
| Place: | Englewood, NJ 07631 | |
| Telephone: | (800) 662-6383 | Telefax: (201) 894-0213 |
| e-mail: | info@dmg-america.com | |
| Internet: | www.dmg-america.com | |

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

May cause respiratory irritation.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

2.2. Label elements**Regulation (EC) No. 1272/2008**

Signal word: Warning

Pictograms:

**Hazard statements**

| | |
|------|--------------------------------------|
| H335 | May cause respiratory irritation. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |

Precautionary statements

| | |
|----------------|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P302+P352 | IF ON SKIN: Wash with plenty of water. |

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Plus_-Fluorescence_-Solar

Revision date: 13.04.2016

Product code: 110368, 110400-110404, 110406, 110-585-110589, 110710,
110719, 110722, 110723, 110360 (1300-GHS)

Page 2 of 4

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

Hazardous components

| CAS No | Chemical name | | | Quantity |
|------------|---|----------|----------|----------|
| | EC No | Index No | REACH No | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | | | |
| 41637-38-1 | Dimethacrylate Resin | | | 35-45 % |
| | | | | |
| | | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Avoid exposure. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Medical treatment necessary.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**Keep container tightly closed in a cool, well-ventilated place.
Store only in original container.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Plus_-Fluorescence_-Solar

Revision date: 13.04.2016

Product code: 110368, 110400-110404, 110406, 110-585-110589, 110710,
110719, 110722, 110723, 110360 (1300-GHS)

Page 3 of 4

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Protective and hygiene measures**

When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | | |
|--|----------------|-----------------------|
| Physical state: | Paste | |
| Colour: | characteristic | |
| Odour: | ester | |
| pH-Value (at 20 °C): | | ca. 7 |
| Changes in the physical state | | |
| Initial boiling point and boiling range: | | >250 °C |
| point of decomposition: | | 200 °C |
| Flash point: | | >150 °C |
| Ignition temperature: | | >380 °C |
| Vapour pressure: (at 20 °C) | | 1 hPa |
| Density: | | 1,5 g/cm ³ |
| Water solubility: | | 10 g/L |
| Vapour density: | | 1 |

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

heat. Light.

Decomposition takes place from temperatures above: 200 °C

Decomposition under formation of: Acrylate.

10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

SECTION 11: Toxicological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Luxatemp Plus_-Fluorescence_-Solar

Revision date: 13.04.2016

Product code: 110368, 110400-110404, 110406, 110-585-110589, 110710,
110719, 110722, 110723, 110360 (1300-GHS)

Page 4 of 4

11.1. Information on toxicological effects**Acute toxicity**

LD50: Rat 5000 mg/kg

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

SECTION 12: Ecological information**12.1. Toxicity**

Acute fish toxicity LC50: >360 mg/l/48h

12.2. Persistence and degradability

Preparation not tested.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information**Other applicable information**

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information****SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

| | |
|------|--------------------------------------|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)