

1. IDENTIFICATION

Product Identifier

Product Name JET TOOTH SHADE POWDER

Other means of identification

SDS# 018
Product Code 1410, 1412, 1420, 1430, 1450, 1470, 1480, 1484, 1493

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of provisional crowns and bridges

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.
 175 Messner Dr.
 Wheeling, IL 60090
 USA

Emergency telephone number

Company Phone Number 847-215-6622
Emergency Telephone (INFOTRAC) 352-323-3500 (International)
 800-535-5053 (North America)

Authorized European Representative

MediMark® Europe SARL
 11, rue Emile Zola – BP 2332
 38033 Grenoble Cedex 2
 France
 Tel: +33 476 86 43 22
 Fax: +33 476 17 19 82
 Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

| | |
|-----------------------|----|
| Eye Damage/Irritation | 2A |
| Skin sensitization | 1 |

Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.



Physical State Powder **Appearance** Fine, white or pigmented **Odor** Faint odor in bulk

Precautionary Statements – Prevention

- P261 Avoid breathing dust, fumes, gas, mist, vapors or spray.
- P264 Wash hands and exposed skin thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – Response

P302+P352 IF ON SKIN: Wash with soap and water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.

Precautionary Statements – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

| |
|--|
| 3. COMPOSITION / INFORMATION ON INGREDIENTS |
|--|

| Chemical Name | CAS No | Weight - % |
|--|------------|------------|
| 2-Propenoic acid, 2-methyl-, methyl ester, homopolymer | 9011-14-7 | 80-90 |
| Diethyl phthalate | 84-66-2 | 10-20 |
| Benzoyl Peroxide | 94-36-0 | 1-5 |
| Titanium Dioxide (CI77891) | 13463-67-7 | 0-1 |

*Specific chemical weight has been withheld as a trade secret.

| |
|------------------------------|
| 4. FIRST AID MEASURES |
|------------------------------|

First aid measures

Inhalation Remove to fresh air. Get medical attention if discomfort persists.

Eye contact Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists, get medical advice / attention.

Ingestion Do NOT induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately and provide an estimate of when and how much material was ingested.

Skin Contact Wash with soap and water. If irritation persists, call a physician. Take off contaminated clothing and wash before reuse.

Most important symptoms and effects, both acute and delayed

Symptoms Skin contact may aggravate an existing dermatitis. Direct contact with eyes may cause temporary irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

| |
|----------------------------------|
| 5. FIRE-FIGHTING MEASURES |
|----------------------------------|

Extinguishing Media

Suitable: Water, carbon dioxide (CO₂), dry chemical
Unsuitable: Avoid extinguishing methods which may generate dust clouds.

Specific hazards arising from the chemical

For bulk size: Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust.

Protective equipment and precautions for firefighters

Self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove any contaminated clothing and wash thoroughly before reuse.

Methods and material for containment and clean-up

Method for containment Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material, sand or earth. May contaminate water supply.

Method for clean-up Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills. Clean up in accordance with all applicable regulations. Wash all affected areas with plenty of warm water and soap.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use only in well-ventilated areas. Avoid contact with skin, eyes or clothing. Avoid breathing dust or fume. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed to prevent water absorption and contamination. Store in a dry, cool and well-ventilated place away from direct sunlight or other sources of light or intense heat. Temperature not to exceed 35°C.

Packaging materials Keep in original container.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---|---------------------------|--|--------------------------|
| 2-Propenoic acid, 2-methyl-, methyl ester, homopolymer 9011-14-7 | | | |
| Diethyl phthalate 84-66-2 | TWA: 5 mg/m ³ | TWA: 5 mg/m ³ | TWA: 5 mg/m ³ |
| Benzoyl peroxide 94-36-0 | TWA: 5 mg/m ³ | TWA: 5 mg/m ³ | TWA: 5 mg/m ³ |
| Titanium Dioxide (CI77891) 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ (total dust) | |

Appropriate engineering controls

Apply technical measures to comply with the occupational exposure limits. When working with large quantities of product, provide adequate ventilation (e.g. local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers.

Individual protection measures, such as personal protective equipment

Eye / face protection

Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to US OSHA 29 CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

| | |
|---------------------------------------|---|
| Skin and body protection | If anticipated that prolonged and repeated skin contact will occur during use of this product, wear gloves for routine industrial use. If necessary, refer to US OSHA 29 CFR SS1910.138 or the appropriate standards of Canada or the EC member states. |
| Respiratory protection | No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per US OSHA requirement in 29 CFR SS 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its provinces, EC member states or Australia. VENTILATION: Local exhaust at processing equipment. |
| General hygiene considerations | Handle in accordance with good industrial hygiene and safety practice. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|--------------------------------------|--------------------|-------------|--------------------|
| Physical state | Powder | Odor | Faint odor in bulk |
| Appearance | Fine | | |
| Color | White or pigmented | | |
| Property | Values | | |
| Boiling point / boiling range | 295°C | | |
| Auto ignition temperature | 80°C | | |
| Flash point | 303°C / 577°F | | |
| Flammability limits in air | | | |
| Upper flammability limit | Not applicable | | |
| Lower flammability limit | Not applicable | | |
| Specific gravity | 0.00 | | |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | Not reactive under normal conditions |
| Chemical stability | Stable under recommended storage conditions |
| Possibility of hazardous reactions | None under normal processing |
| Hazardous polymerization | Does not occur. |
| Conditions to avoid | Heating above 240°C / 464°F |
| Incompatible materials | Strong oxidizing agents |
| Hazardous decomposition products | Methacrylate monomer, oxides of carbon when burned |

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

| | |
|----------------------------|---|
| Product information | This product has not been tested on animals to obtain toxicology data. |
| Inhalation | Not expected to be an inhalation hazard under normal conditions of intended use |
| Eye contact | Avoid contact with eyes. |
| Skin contact | Avoid contact with skin. |
| Ingestion | Do not taste or swallow. |

Information on physical, chemical and toxicological effects

| | |
|-----------------|----------------|
| Symptoms | See Section 4. |
|-----------------|----------------|

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|----------------------------------|---|
| Component Carcinogenicity | Titanium Dioxide (CI77891) 13463-67-7 % Weight : 0.1 to 1.0% NIOSH: Potential occupational carcinogen IARC: Possible human carcinogen OSHA: Listed |
|----------------------------------|---|

12. ECOLOGICAL INFORMATION

Component Ecotoxicity There is no specific data available for this product; however, very large releases may be harmful or fatal to overexposed aquatic life.

For Diethyl Phthalate:

| | | | | | |
|----------------------|-------------------------|------------------------|---------------------------------|------------------------|-------------------------|
| Pimephales promeias | 96 Hr: LC ₅₀ | 17 mg/L (flow-through) | Desmodesmus subspicatus | 72 Hr EC ₅₀ | 23 mg/L |
| Pimephales promeias | 96 Hr: LC ₅₀ | 16.8 mg/L (static) | Desmodesmus subspicatus | 72 Hr EC ₅₀ | 23 mg/L |
| Lepornis macrochirus | 96 Hr: LC ₅₀ | 16.7 mg/L (static) | Desmodesmus subspicatus | 96 Hr EC ₅₀ | 21 mg/L |
| Onchorhynchus mykiss | 96 Hr: LC ₅₀ | 12 mg/L (flow-through) | Desmodesmus subspicatus | 96 Hr EC ₅₀ | 21 mg/L (static) |
| Daphnia magna | 48 Hr: EC ₅₀ | 36-74 mg/L | Pseudokirchneriella subcapitata | 96 Hr EC ₅₀ | 42-255 mg/L |
| Daphnia magna | 48 Hr: EC ₅₀ | 86 mg/L (static) | Pseudokirchneriella subcapitata | 96 Hr EC ₅₀ | 2.11-4.29 mg/L (static) |

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Follow all local and national government regulations in disposing material or contaminated packaging.

Contaminated Packaging For bulk only: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers properly in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

DOT Not regulated
IATA Not regulated
IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

EINECS Listed

TSCA Listed

US Federal Regulations

SARA 302 – Extremely Hazardous – Not Listed

SARA 311 / 312 Hazard Categories – Not Listed

SARA 313 – Toxic Chemicals for Benzoyl peroxide 94-36-0 Listed

US State Regulations

California Proposition 65 – Warning. This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: 13463-67-7 Titanium Dioxide (CI77891) 0.1 to 1.0%

16. OTHER INFORMATION

| HMIS | Health Hazards | Flammability | Physical Hazards |
|------|----------------|--------------|------------------|
| | 1 | 1 | 0 |

Effective Date 28-Sep-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet