

# **SAFETY DATA SHEET**

Effective Date 18-Sep-2020 Version 4

## 1. IDENTIFICATION

**Product Identifier** 

Product Name JET SET-4 LIQUID / RESINCAP LIQUID

Other means of identification

**SDS#** 030 UN/I**D No** UN1993

**Product Code** 3802X6, 3803, 3804, 3807, 3808, 3812, 3893 / 2302, 2307, 2308, 2312

Recommended use of the chemical and restrictions on use

Recommended Use Self-curing acrylic resin

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.

175 Messner Dr. Wheeling, IL 60090

USA

**Emergency telephone number** 

**Company Phone Number** +1-847-215-6622

Emergency Telephone (INFOTRAC) +1-352-323-3500 (International)

800-535-5053 (North America)

<u>Authorized European Representative</u> MediMark® Europe SARL

11, rue Emile Zola – BP 2332 38033 Grenoble Cedex 2

France

Tel: +33 476 86 43 22 Fax: +33 476 17 19 82

Email: info@medimark-europe.com

## 2. HAZARDS IDENTIFICATION

### Classification of the substance or mixture

Flammable liquids	Category 2
Skin Corrosion / Irritation	Category 2
Skin Sensitization	Category 1
Specific Target Organ Toxicity - Single Exposure (Respiratory)	Category 3

Signal word Danger

Hazard statements H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H335 May cause respiratory irritation.



Appearance Clear Physical state Liquid Odor Acrid

#### **Precautionary Statements - Prevention**

P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Precautionary Statements - Response

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before use.

P370+P378 In case of fire: Use CO2, for extinction.

#### Precautionary Statements - Storage

P235 Keep cool.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

## Precautionary Statements - Disposal

P501 Dispose of contents/container in accordance with local regulation.

#### Hazardous component(s) for labeling Contains methyl methacrylate

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
Methyl Methacrylate	80-62-6	<90	*
2-Hydroxyethyl Methacrylate	868-77-9	<20	*
N, N-Dimethyl-p-Toluidine	99-97-8	<2	*

<sup>\*</sup>Specific chemical weight has been withheld as a trade secret.

# 4. FIRST AID MEASURES

First aid measures

Inhalation Remove victim to fresh air. Keep at rest in a position comfortable for breathing. Seek immediate medical

attention.

Eye contact Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists,

call a physician immediately.

Ingestion If ingested, do not induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer

water or milk. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately and provide an estimate of when and how much material was ingested. Seek immediate

medical attention.

**Skin Contact**Wash with soap and water. If irritation, redness or swelling persists, call a physician immediately. Take off

contaminated clothing and wash before reuse.

## Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

#### **Extinguishing Media**

Suitable: Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide,

**Unsuitable:** Water spray or water stream may not be effective.

### Specific hazards arising from the chemical

For bulk size >1L – High temperatures, inhibitor depletion, accidental impurities, or exposure to radiation or oxidizers may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. This product is flammable liquid. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Vapor forms an explosive mixture with air.

#### **Hazardous Combustion Products**

Acrid smoke-fumes/carbon monoxide/carbon dioxide and perhaps other toxic vapors may be released during a fire involving this product.

#### **Special Fire Fighting Procedures**

Use a water spray or fog to reduce or direct vapors, and keep containers cool. Water may not be effective in actually extinguishing a fire involving this product. Do not enter fire area without proper protection. Fight fire from a safe location. Structural firefighters must wear SCBAs and full protective equipment. Heat/Impurities may cause pressure to build and/or rupture closed containers, spreading fire, increasing risk of burns/injuries.

### Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus for firefighting if necessary. Do not enter area without proper protection. Fight fire from safe distance/protected location. Heat /impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray to cool unopened containers. Pressure relief system may plug with solids creating risk of overpressure.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions**Before cleaning any spill or leak, individuals must wear personal protective equipment as required.

Remove any contaminated clothing and wash thoroughly before reuse.

Environmental precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Prevent

product from entering drains. Spillages or uncontrolled discharges into watercourses must be

alerted to the appropriate regulatory body.

### Methods and material for containment and clean-up

**Method for containment** Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material.

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. DO NOT use combustible materials such as sawdust. May contaminate water supply.

Method for clean-up Maximize ventilation (open doors and windows) and secure all sources of ignition. Place into

appropriate closed container(s) for disposal in accordance with local, state and federal regulations.

Wash all affected areas with plenty of warm water and soap.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling

Keep away from heat, sparks, and flame. Keep container closed after each use. Avoid contact with

skin, eyes and clothing. Use good personal hygiene and housekeeping. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling product. Keep away from heat, sparks, and flame. Keep container closed after each use. Ground and bond all

containers when transferring. Observe precautions found on the label.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition. Protect from direct sunlight. Keep container closed to prevent water absorption and contamination. Methacrylate stored in bulk quantities must be kept in

contact with air (oxygen). Keep at temperature not exceeding 30°C/86 °F.

Packaging materials Keep in original container.

Incompatible materials Strong oxidizing agents, strong reducing agents, free-radical generators, inert gases, oxygen

scavengers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure guidelines**

Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. The following information is given as general guidance.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Methyl Methacrylate	STEL: 100 ppm	TWA:100 ppm	TWA:100 ppm
80-62-6	TWA: 50 ppm	TWA: 410 mg/m <sup>3</sup>	TWA: 410 mg/m <sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists / OSHA = Occupational Safety and Health Administration PEL = Permissible Exposure Levels / STEL - Short Term Exposure Limit / TLV - Threshold Limit Value / TWA = Time Weighted Average

Appropriate engineering controls

**Engineering controls** For bulk size: Use local explosion-proof ventilation that is adequate to keep employee exposure to

airborne concentrations below exposure limits.

Individual protection measures, such as personal protective equipment

Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to Eye / face protection

US OSHA 29CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure

that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and body protection If anticipated that prolonged and repeated skin contact will occur during use of this product, wear

> gloves for routine industrial use. If necessary, refer to US OSHA 29CFR SS1910.138 or the appropriate standards of Canada or the EC member states. Wear suitable protective clothing.

Respiratory protection No special respiratory protection is required under typical circumstances of use or handling. If

necessary, use only respiratory protection authorized per US OSHA requirement in 29 CFR SS 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its provinces, or the EC member states. VENTILATION: Local exhaust at processing equipment.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after

> handling. Food, beverages and tobacco products should not be carried, stored, or consumed where this material is in use. Wash hands thoroughly before eating, drinking, or smoking.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state Liquid Odor Acrid

**Appearance** Liquid Odor threshold Not determined

Color Clear

Remarks / Method **Property Values** 

Not determined Melting point / Freezing point Not determined 101°C / 214° F Boiling point / boiling range Flash point 12°C / 54°F **Evaporation rate** Not determined

Flammability (solid, gas) n/a (liquid) Flammability limits in air

Not applicable Upper flammability limit Lower flammability limit Not applicable

Specific gravity 0.967 Water = 1

Autoignition temperature 421°C / 790°F Other information

Density 0.967 g/mL

## 10. STABILITY AND REACTIVITY

Reactivity Unstable/Reactive upon depletion of inhibitor.

**Chemical stability** Stable under recommended storage conditions. Possibility of hazardous reactions None under normal processing

Hazardous polymerization Hazardous polymerization may occur.

### Incompatible materials

Strong oxidizing agents, strong reducing agents, free-radical generators, inert gases, oxygen scavengers Material has strong solvent properties and can soften paint and rubber.

Hazardous decomposition products Carbon oxides

## 11. TOXICOLOGICAL INFORMATION

**Mixture Toxicity** Inhalation Toxicity: 4,632 mg/L

Component Toxicity No data available Routes of Exposure - No data available Target Organs - Eyes, Skin, Respiratory System Inhalation Harmful if inhaled.

Eve contact

Causes severe eye irritation.

Skin contact Causes skin irritation. May be harmful in contact with skin.

Ingestion May be harmful if swallowed.

Product Components Listed as Carcinogenic None

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Algae / aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Methyl	170: 96 h	243-275: 96 h Pimephales promelas mg/L	-	69: 48 h Daphnia magna
Methacrylate	Pseudokirchneriella	LC50 flow-through;		mg/L EC50
80-62-6	subcapitata mg/L EC50	125.5-190.7: 96 h Pimephales		_
		promelas mg/L LC50 static;		
		170-206: 96 h Lepomis macrochirus mg/L		
		LC50 flow-through;		
		153.9-341.8: 96 h Lepomis macrochirus mg/L		
		LC50 static;		
		326.4-426.9 96 h Poecilia reticulata mg/L		
		LC50 static;		
		>79: 96 h Oncorhynchus mykiss mg/L LC50		
		flow-through;		
		>79: 96 h Oncorhynchus mykiss mg/L LC50		
		static		

## 13. DISPOSAL CONSIDERATIONS

## Waste treatment methods

#### Disposal of wastes

Follow all local and national government regulations in disposing material or contaminated packaging.

For U.S. - Dispose of in accordance with federal, state and local regulations. When discarded, it is considered a hazardous waste by the EPA under RCRA. The reportable quantity for methyl methacrylate is 1000 lb. (40 CFR Part 302). Add excess inhibitor before disposing.

### **Contaminated Packaging**

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers in accordance with local and national government regulations.

## 14. TRANSPORTATION INFORMATION

## DOT

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl Methacrylate monomer, stabilized /
	N,N-Dimethyl-p-Toluidine solution)
Hazard Class	3
Packing Group	
Reportable Quantity (RQ)	1000 lb. (methyl methacrylate)

#### **IATA**

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl Methacrylate monomer, stabilized / N,N-Dimethyl-p-Toluidine solution)
Hazard Class	3
Packing Group	

#### **IMDG**

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl Methacrylate monomer, stabilized / N,N-Dimethyl-p-Toluidine solution)
Hazard Class	3
Packing Group	

## 15. REGULATORY INFORMATION

#### International Inventories

Methyl methacrylate 80-62-6

TSCA Listed United States Toxic Substances Control Act, Section 8(b) Inventory

**DSL** Listed Canadian Domestic Substances List

EINECS Listed European Inventory of Existing Chemical Substances

**EU Regulations** EC No. 1272/2008 (CLP) Classification, Labeling, Packaging

Medical Devices Directive 93/42/EEC - Class I Medical Devices

<u>US Federal Regulations</u> SARA 302 – Extremely hazardous substance - not listed

SARA 311/312 - Hazard categories - listed Methyl methacrylate 80-62-6

SARA 313 - Methyl Methacrylate 80-62-6

<u>US State Regulations</u> California Proposition 65 – Warning. This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: None

US State Right-to-Know Regulations Not established

## 16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability
	2	3	2
HMIS	Health Hazards	Flammability	Physical Hazards
	2	3	2

Effective Date 18-Sept-2020

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



# SAFETY DATA SHEET

Effective Date 24-Apr-23 Version 4

## 1. IDENTIFICATION

**Product Identifier** 

Product Name JET SET-4 TOOTH SHADE POWDER

Other means of identification

**SDS#** 023

**Product Code** 3810, 3812, 3820, 38H0, 3830, 3850, 3870, 3893

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of provisional crowns and bridges

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.

175 Messner Dr. Wheeling, IL 60090

USA

**Emergency telephone number** 

Company Phone Number 1-847-215-6622

Emergency Telephone (INFOTRAC) 1-352-323-3500 (International)

800-535-5053 (North America)

Authorized European Representative MediMark® Europe SARL

11, rue Emile Zola – BP 2332 38033 Grenoble Cedex 2

France

Tel: +33 476 86 43 22 Fax: +33 476 17 19 82

Email: info@medimark-europe.com

## 2. HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

Eye Damage/Irritation	2B
Skin sensitization	1

Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.

H320 Causes eye irritation.



Physical State Powder Appearance Fine, white or pigmented Odor Faint odor in bulk

**Precautionary Statements - Prevention** 

P261 Avoid breathing dust, fumes, gas, mist, vapors or spray.

P264 Wash hands and exposed skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

P302+P352 IF ON SKIN: Wash with soap and water.

P305+P351 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy

+P338 to do – continue rinsing.

P308+P313 If exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists, get medical advice/attention.

P363 Wash contaminated clothing before reuse.

#### Precautionary Statements - Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
Polymer	9011-14-7	< 90	*
Polymer	9003-42-3	< 90	*
Benzoyl Peroxide	94-36-0	< 2	

<sup>\*</sup>Specific chemical weight has been withheld as a trade secret.

## 4. FIRST AID MEASURES

First aid measures

Inhalation Remove to fresh air. Keep at rest in a position comfortable for breathing. Get medical attention if discomfort

persists.

**Eye contact** Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists,

get medical advice / attention.

Ingestion Do NOT induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer water or milk.

Never give anything by mouth to an unconscious person. Call a physician or poison control center

immediately and provide an estimate of when and how much material was ingested.

Skin Contact Wash with soap and water. If irritation persists, call a physician. Take off contaminated clothing and wash

before reuse.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** Skin contact may aggravate an existing dermatitis. Direct contact with eyes may cause temporary irritation.

#### Indication of any immediate medical attention and special treatment needed

## 5. FIRE-FIGHTING MEASURES

#### **Extinguishing Media**

Suitable: Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide (CO<sub>2</sub>).

**Unsuitable:** Water may not be effective in extinguishing this fire.

#### Specific hazards arising from the chemical

For bulk size: Polymers are combustible dusts; care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.

#### **Special Fire Fighting Procedures:**

Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus.

#### Protective equipment and precautions for firefighters

For bulk size: Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static charge, follow grounding and bounding procedures. Polymers are not sensitive to mechanical impacts.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

thoroughly before reuse.

#### Methods and material for containment and clean-up

Method for containment Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material, sand

or earth. May contaminate water supply.

Method for clean-up Sweep up to avoid slippin

Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills. Clean up in accordance with all applicable regulations. Wash all affected areas with plenty of

warm water and soap.

## 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use only in well-ventilated areas. Avoid contact with skin, eyes or clothing. Avoid breathing dust or

fume. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed to prevent water absorption and contamination. Store in a dry, cool

and well-ventilated place away from direct sunlight or other sources of light or intense heat.

Temperature not to exceed 35°C.

Packaging materials Keep in original container.

Incompatible materials Strong oxidizing agents

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Appropriate engineering controls

Apply technical measures to comply with the occupational exposure limits. When working with

large quantities of product, provide adequate ventilation (e.g. local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers.

Individual protection measures, such as personal protective equipment

Eye / face protection Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to

US OSHA 29 CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure

that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and body protection If anticipated that prolonged and repeated skin contact will occur during use of this product, wear

gloves for routine industrial use. If necessary, refer to US OSHA 29 CFR SS1910.138 or the

appropriate standards of Canada or the EC member states.

Respiratory protection No special respiratory protection is required under typical circumstances of use or handling. If

necessary, use only respiratory protection authorized per US OSHA requirement in 29 CFR SS 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its

provinces, EC member states or Australia. VENTILATION: Local exhaust at processing equipment.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical statePowderOdorFaint odor in bulkAppearanceFineOdor thresholdNot determined

**Color** White or pigmented

Property Values Remarks / Method

Evaporation rate
Vapor pressure
Vapor density
Specific gravity
Water solubility

Not applicable
Not applicable
Not determined
Insoluble in water

## 10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

Chemical stability Stable under recommended storage conditions

Possibility of hazardous reactions

None under normal processing

Hazardous polymerization Incompatible materials Does not occur. Strong oxidizing agents

Hazardous decomposition products

Methacrylate monomer, oxides of carbon when burned

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposures

**Product information** This product has not been tested on animals to obtain toxicology data.

Inhalation Not expected to be an inhalation hazard under normal conditions of intended use

Eye contact
Skin contact
Avoid contact with eyes.
Avoid contact with skin.
Ingestion
Do not taste or swallow.

#### Information on physical, chemical and toxicological effects

**Symptoms** See Section 4.

#### 12. ECOLOGICAL INFORMATION

<u>Component Ecotoxicity</u> There is no specific data available for this product; however, very large releases may be harmful or fatal to

overexposed aquatic life.

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Follow all local and national government regulations in disposing material or contaminated

packaging.

Contaminated Packaging For bulk only: Reuse of empty drums or containers is not recommended. Employees should be

advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers properly in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

DOTNot regulatedIATANot regulatedIMDGNot regulated

## 15. REGULATORY INFORMATION

#### International Inventories

EINECS This product is a medical device and not subject to chemical notification requirements.

TSCA For use in FDA regulated products only United States Toxic Substances Control Act, Section 8(b) Inventory

## **US Federal Regulations**

TSCA This product is an FDA regulated device and not subject to TSCA regulations.

SARA 302 - Extremely Hazardous - Not Listed

SARA 311 / 312 Hazard Categories - This product is an FDA regulated device and not subject to reporting requirements.

# **16. OTHER INFORMATION**

HMIS	Health Hazards	Flammability	Physical Hazards
	1	1	0

Effective Date 24-Apr-2023

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet