

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199 Denture Base Powder

Lucitone 199 Repair Powder

Lucitone Fas-Por +, Powder

Lucitone Clear Dental Resin Powder

Lucitone Clear Pour Acrylic Powder

Lucitone Intensive Colors

Version: **1.13 / GB**
Revision date: **25.10.2018**
Issue date: **14.02.2003**
replaces version: **1.12**
Page: **1 / 9**

Material no. **0D905930**
Specification **142125**
VA-Nr **01804105**



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
Lucitone 199 Denture Base Powder
Lucitone 199 Repair Powder
Lucitone Fas-Por +, Powder
Lucitone Clear Dental Resin Powder
Lucitone Clear Pour Acrylic Powder
Lucitone Intensive Colors

REACH Registration No.: if available listed in Chapter. 3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant applications identified For dental use only.

1.3. Details of the supplier of the safety data sheet

Company
DeguDent GmbH
Postfach 1364
D-63403 Hanau

Telephone
+49 (0)6181/59-5767
Telefax
+49 (0)6181/59-5879
Email address
SDB.Degudent-DE@dentsplysirona.com

1.4. Emergency telephone number

Emergency information +49 (0)6181/59-50 (This telephone number is available during office hours only.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not a hazardous mixture according to Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling as per (EU) 1272/2008

Statutory basis Labelling not required according to EU-CLP Ordinance (1272/2008).

2.3. Other hazards

Mechanical irritation of skin and mucous linings of eyes and respiratory tract may occur., Danger of dust explosion.
A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

SECTION 3: Composition/information on ingredients

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199 Denture Base Powder
Lucitone 199 Repair Powder
Lucitone Fas-Por +, Powder
Lucitone Clear Dental Resin Powder
Lucitone Clear Pour Acrylic Powder
Lucitone Intensive Colors

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 2 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105



3.1. Substances

-

3.2. Mixtures

Information on ingredients / Hazardous components as per EU-CLP Regulation (EC) No. 1272/2008

• Poly(methyl methacrylate)	95% - 100%
CAS-No. 9011-14-7	

Texts of H phrases, see in Chapter 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Remove contaminated or saturated clothing.

Inhalation

In case product dust is released:

Move victims into fresh air.

In case of persistent discomfort

Obtain medical attention.

Skin contact

Wash off with soap and plenty of water.

Eye contact

Possible discomfort is due to foreign substance effect.

Rinse thoroughly with plenty of water keeping eyelid open.

In case of persistent discomfort

Consult an ophthalmologist.

Ingestion

Rinse mouth.

After absorbing large amounts of substance:

Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

After absorbing large amounts of substance:

Acceleration of gastrointestinal passage

If skin sensitisation has developed and a causal relationship has been confirmed, further exposure should not be allowed

SECTION 5: Firefighting measures

5.1. Extinguishing media

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199 Denture Base Powder
Lucitone 199 Repair Powder
Lucitone Fas-Por +, Powder
Lucitone Clear Dental Resin Powder
Lucitone Clear Pour Acrylic Powder
Lucitone Intensive Colors

Version:	1.13 / GB	Material no.	0D905930
Revision date:	25.10.2018	Specification	142125
Issue date:	14.02.2003	VA-Nr	01804105
replaces version:	1.12		
Page:	3 / 9		



Suitable extinguishing media: mist
Foam
quenching powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media: High volume water jet

5.2. Special hazards arising from the substance or mixture

May be released in case of fire: carbon monoxide, carbon dioxide, organic products of decomposition.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No particular measures required.

6.2. Environmental precautions

Do not allow entrance in sewage water, soil stretches of water, groundwater, drainage systems.

6.3. Methods and material for containment and cleaning up

Pick up mechanically and collect in a suitable container. Avoid formation of dust.

Sweep up to prevent slipping hazard.

Clean up promptly by scoop or vacuum.

Additional advice

Danger of slipping due to leaking or spilt product.

Ensure explosion proofness. Dispose of contaminated material as a waste in a correct manner.

6.4. Reference to other sections

Disposal considerations; see section 13.

Wear personal protective equipment; see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid dust formation.

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Danger of dust explosion.

Caution - electrostatic charge may occur.

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Storage

Keep in a dry place.

German storage class

13 - Non Combustible Solids

7.3. Specific end use(s)

We are unaware of any specific end uses which go beyond the data reported in Section 1.

SECTION 8: Exposure controls/personal protection

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199 Denture Base Powder
Lucitone 199 Repair Powder
Lucitone Fas-Por +, Powder
Lucitone Clear Dental Resin Powder
Lucitone Clear Pour Acrylic Powder
Lucitone Intensive Colors

Version: **1.13 / GB**
Revision date: **25.10.2018**
Issue date: **14.02.2003**
replaces version: **1.12**
Page: **4 / 9**

Material no. **0D905930**
Specification **142125**
VA-Nr **01804105**



8.1. Control parameters

• exposure limit for dust		
CAS-No.		
Control parameters	10 mg/m3	(EH40 WEL)
type of exposure	Inhalable fraction.	
Control parameters	4 mg/m3	(EH40 WEL)
type of exposure	Respirable fraction.	

8.2. Exposure controls

Engineering measures

In case product dust is released:, Local ventilation.

Personal protective equipment

Respiratory protection

If workplace exposure limit is exceeded apply Dust mask with P2 particle filter.

Hand protection

Wear protective gloves made of the following materials:.

Glove material butyl-rubber

Material thickness 0.5 mm

Break through time 60 min

The suitability for a specific workplace should be discussed with the producers of the protective gloves.,

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Preventive skin protection, Use barrier cream regularly.

Eye/face protection

Safety glasses with side-shields, If dust occurs: basket-shaped glasses

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice., Do not eat, drink, smoke, or sniff while at work. Wash your hands and/or face before breaks and before termination of work., If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form powder

Colour depending on staining result

Odour characteristic

Odour threshold: no data available

pH not applicable
(solid)

Melting point/range > 210 °C

Boiling point/range no data available

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version:	1.13 / GB	Material no.	0D905930
Revision date:	25.10.2018	Specification	142125
Issue date:	14.02.2003	VA-Nr	01804105
replaces version:	1.12		
Page:	5 / 9		



Flash point	not applicable (solid)
Evaporation rate	not applicable, (solid)
Flammability (solid, gas)	no data available
Lower explosion limit	no data available
Upper explosion limit	no data available
Vapour pressure	not applicable (solid)
Density	no data available
Water solubility	insoluble
Partition coefficient: n-octanol/water	not applicable
Autoinflammability	Not capable of spontaneous combustion or heating.
Thermal decomposition	250 °C
Viscosity, dynamic	not applicable (solid)
Explosiveness	Dusts might form explosive mixtures with air.
Oxidizing properties	no data available

9.2. Other information

Bulk density	325 - 375 kg/m ³	(20 °C)
Other information	No further physicochemical data were determined.	

SECTION 10: Stability and reactivity**10.1. Reactivity**

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No hazardous reactions are known if properly handled and stored.
------------------------------------	--

10.4. Conditions to avoid

None known

10.5. Incompatible materials

None known

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199 Denture Base Powder

Lucitone 199 Repair Powder

Lucitone Fas-Por +, Powder

Lucitone Clear Dental Resin Powder

Lucitone Clear Pour Acrylic Powder

Lucitone Intensive Colors

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 6 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105



10.6. Hazardous decomposition products

decomposition products if heated above 250°C

irritative gases/vapours, Carbon monoxide, Carbon dioxide (CO₂), organic products of decomposition

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No results of animal experiments with the product available.

Acute oral toxicity no data available

Acute inhalation toxicity no data available

Acute dermal toxicity no data available

Skin irritation no data available

Eye irritation no data available

Sensitization no data available

Assessment of STOT single exposure no data available

Assessment of STOT repeat exposure no data available

Risk of aspiration toxicity not applicable

Mutagenicity assessment no data available

Carcinogenicity No data available

Toxicity to reproduction No data available

Human experience Mechanical irritation of skin and mucous linings of eyes and respiratory tract may occur.

Toxicology Assessment

Acute effects An Expert Judgment stated that no classification is necessary based on present knowledge.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological tests with this preparation are not available.

12.2. Persistence and degradability

Biodegradability No data available

12.3. Bioaccumulative potential

Bioaccumulation No data available

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199 Denture Base Powder
Lucitone 199 Repair Powder
Lucitone Fas-Por +, Powder
Lucitone Clear Dental Resin Powder
Lucitone Clear Pour Acrylic Powder
Lucitone Intensive Colors

Version: **1.13 / GB**
Revision date: **25.10.2018**
Issue date: **14.02.2003**
replaces version: **1.12**
Page: **7 / 9**

Material no. **0D905930**
Specification **142125**
VA-Nr **01804105**

**12.4. Mobility in soil**

Mobility

Is absorbed by the soil and is not mobile.

The product is a high-molecular-weight, water insoluble, solid polymer.

12.5. Results of PBT and vPvB assessment

A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

12.6. Other adverse effects

Further Information

The product is a solid, insoluble in water, chemically inert and virtually not biologically degradable.

No negative effects known.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Product**

Disposal according to local authority regulations.

Uncleaned packaging

Disposal according to local authority regulations.

SECTION 14: Transport information**Not dangerous according to transport regulations.**

- | | |
|-------------------------------------|----|
| 14.1. UN number: | -- |
| 14.2. UN proper shipping name: | -- |
| 14.3. Transport hazard class(es): | -- |
| 14.4. Packing group: | -- |
| 14.5. Environmental hazards: | -- |
| 14.6. Special precautions for user: | No |

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National legislation****15.2. Chemical safety assessment**

Chemical safety assessment No Chemical Safety Report as per Articles 2(8), 2(9) or 14 of the REACH Regulation is required for this product.

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199 Denture Base Powder

Lucitone 199 Repair Powder

Lucitone Fas-Por +, Powder

Lucitone Clear Dental Resin Powder

Lucitone Clear Pour Acrylic Powder

Lucitone Intensive Colors

Version: 1.13 / GB
Revision date: 25.10.2018
Issue date: 14.02.2003
replaces version: 1.12
Page: 8 / 9

Material no. 0D905930
Specification 142125
VA-Nr 01804105



SECTION 16: Other information

Classification and applied procedure to derive the classification of mixtures according to EU Regulation (EC) No. 1272/2008 (CLP)

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Legend

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ASTM	American Society for Testing and Materials
ATP	Adaptation to Technical Progress
BCF	Bioconcentration factor
BetrSichV	German Ordinance on Industrial Safety and Health
c.c.	closed cup
CAS	Chemical Abstract Services
CESIO	European Committee of Organic Surfactants and their Intermediates
ChemG	German Chemicals Act
CMR	carcinogenic-mutagenic-toxic for reproduction
DIN	German Institute for Standardization
DMEL	Derived minimum effect level
DNEL	Derived no effect level
EINECS	European Inventory of Existing Commercial Chemical Substances
EC50	half maximal effective concentration
GefStoffV	German Ordinance on Hazardous Substances
GGVSEB	German ordinance for road, rail and inland waterway transportation of dangerous goods
GGVSee	German ordinance for sea transportation of dangerous goods
GLP	Good Laboratory Practice
GMO	Genetic Modified Organism
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
ISO	International Organization For Standardization
LOAEL	Lowest observed adverse effect level
LOEL	Lowest observed effect level
NOAEL	No observed adverse effect level
NOEC	no observed effect concentration
NOEL	no observed effect level
o. c.	open cup

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199 Denture Base Powder****Lucitone 199 Repair Powder****Lucitone Fas-Por +, Powder****Lucitone Clear Dental Resin Powder****Lucitone Clear Pour Acrylic Powder****Lucitone Intensive Colors**

Version:	1.13 / GB	Material no.	0D905930
Revision date:	25.10.2018	Specification	142125
Issue date:	14.02.2003	VA-Nr	01804105
replaces version:	1.12		
Page:	9 / 9		



OECD	Organisation for Economic Cooperation and Development
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative, toxic
PEC	Predicted effect concentration
PNEC	Predicted no effect concentration
REACH	REACH registration
RID	Convention concerning International Carriage by Rail
STOT	Specific Target Organ Toxicity
SVHC	Substances of Very High Concern
TA	Technical Instructions
TPR	Third Party Representative (Art. 4)
TRGS	Technical Rules for Hazardous Substances
VCI	German chemical industry association
vPvB	very persistent, very bioaccumulative
VOC	volatile organic compounds
VwVwS	German Administrative Regulation on the Classification of Substances Hazardous to Waters into Water Hazard Classes
WGK	Water Hazard Class
WHO	World Health Organization

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199, Liquid

Lucitone 199 Repair Material, Liquid

Lucitone FAS-POR, Liquid

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **1 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
Lucitone 199, Liquid
Lucitone 199 Repair Material, Liquid
Lucitone FAS-POR, Liquid

REACH Registration No.: if available listed in Chapter. 3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant applications identified For dental use only.

1.3. Details of the supplier of the safety data sheet

Company
DeguDent GmbH
Postfach 1364
D-63403 Hanau

Telephone +49 (0)6181/59-5767
Telefax +49 (0)6181/59-5879
Email address SDB.Degudent-DE@dentsplysirona.com

1.4. Emergency telephone number

Emergency information +49 (0)6181/59-50 (This telephone number is available during office hours only.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids	Category 2	H225
Skin corrosion/irritation	Category 2	H315
Skin Sensitisation	Category 1	H317
Specific Target Organ Toxicity - Single exposure (inhalation)	Category 3	H335

2.2. Label elements

Labelling as per (EU) 1272/2008

Statutory basis EU-CLP as per Regulation (EU) No. 1272/2008, Annex VI

hazard-defining component(s) (GHS)

- methyl methacrylate
- ethylene dimethacrylate

Hazard pictograms



SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199, Liquid

Lucitone 199 Repair Material, Liquid

Lucitone FAS-POR, Liquid

Version: 3.12 / GB
Revision date: 13.11.2017
Issue date: 14.02.2003
replaces version: 3.11
Page: 2 / 12

Material no. 0D682007
Specification 142124
VA-Nr 01779070



Signal word	Danger
Hazard statement	H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation.
Precautionary statement: Prevention	P280 - Wear protective gloves/ eye protection/ face protection. P260 - Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautionary statement: Storage	P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Precautionary statement: Disposal	P501 - Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

When heated, formation of explosive vapour/air mixtures., Danger of bursting of closed systems to vigorous exothermic polymerization. Avoid uncontrolled polymerization.
A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

SECTION 3: Composition/information on ingredients

Chemical nature

The preparation contains:, stabilisers

3.1. Substances

-

3.2. Mixtures

Information on ingredients / Hazardous components as per EU-CLP Regulation (EC) No. 1272/2008

• methyl methacrylate		80% - 100%			
CAS-No.	80-62-6	EC-No.	201-297-1		
Flammable liquids				Category 2	H225
Skin corrosion/irritation				Category 2	H315
Skin Sensitisation				Category 1	H317
Specific Target Organ Toxicity - Single exposure (inhalation)				Category 3	H335
• ethylene dimethacrylate		1% - 20%			
CAS-No.	97-90-5	EC-No.	202-617-2		
Skin Sensitisation				Category 1	H317
Specific Target Organ Toxicity - Single exposure				Category 3	H335

Texts of H phrases, see in Chapter 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Take off all contaminated clothing immediately.

Inhalation

Move victims into fresh air.
Obtain medical attention.

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199, Liquid

Lucitone 199 Repair Material, Liquid

Lucitone FAS-POR, Liquid

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **3 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**



Skin contact

Wash off immediately with soap and plenty of water.
Obtain medical attention.

Eye contact

With eye held open, thoroughly rinse immediately with plenty of water for at least 5 minutes.
Consult an ophthalmologist.

Ingestion

Do NOT induce vomiting.
Have the mouth rinsed with water.
Have patient drink plenty of water in small sips.
Obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

If skin sensitisation has developed and a causal relationship has been confirmed, further exposure should not be allowed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: quenching powder
Carbon dioxide (CO₂)
Alcohol-resistant foam

Unsuitable extinguishing media: Water

5.2. Special hazards arising from the substance or mixture

In case of combustion or decomposition of the product, the fumes produced lead to irritations or inflammations of the respiratory tract.
When heated, formation of explosive vapour/air mixtures.

5.3. Advice for firefighters

In case of fire cool containers or take them to a safe place.
Use water spray to cool unopened containers.
In the case of fire, wear respiratory protective equipment independent of surrounding air and chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep unauthorized persons away.
Wear personal protective equipment.
Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

Prevent substance from entering soil, natural bodies of water and sewer systems., Avoid penetration into drainage system or in rooms situated at a lower level because of danger of explosion.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition.
Absorb with liquid-binding material, e.g. inert absorbent, sand, universal binding agents.
Pick up mechanically with a suitable device and collect in a suitable container.

Additional advice

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199, Liquid

Lucitone 199 Repair Material, Liquid

Lucitone FAS-POR, Liquid

Version: 3.12 / GB
Revision date: 13.11.2017
Issue date: 14.02.2003
replaces version: 3.11
Page: 4 / 12

Material no. 0D682007
Specification 142124
VA-Nr 01779070



Ensure explosion proofness. Dispose of contaminated material as a waste in a correct manner.

6.4. Reference to other sections

Wear personal protective equipment; see section 8.

Disposal considerations; see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Always close container tightly after removal of product.

Avoid light effect heat sun rays.

Vapors are heavier than air.

Only fill up to 90 % of the container as air is required to stabilize.

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

product is highly flammable.

Vapours are heavier than air and may spread along floors.

Formation of flammable or explosive vapour/air mixtures possible. Danger of explosion

Explosion-proof installations required.

Take precautionary measures against static discharges.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place.

Ensure there is good room ventilation.

German storage class

3 - Flammable liquids

7.3. Specific end use(s)

We are unaware of any specific end uses which go beyond the data reported in Section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

• methyl methacrylate			
CAS-No.	80-62-6	EC-No.	201-297-1
Control parameters	100 ppm 416 mg/m3		Short Term Exposure Limit (STEL):(EH40 WEL)
Control parameters	50 ppm 208 mg/m3		Time Weighted Average (TWA):(EH40 WEL)

8.2. Exposure controls

Engineering measures

Ensure suitable suction/aeration at the work place and with operational machinery.

Personal protective equipment

Respiratory protection

If workplace exposure limit is exceeded apply Respirator with brown A-type filter.

Hand protection

Wear protective gloves made of the following materials: solvent-resistant material.

Glove material butyl-rubber

Material thickness 0.5 mm

Break through time 60 min

Method Source: GESTIS substance database (hazardous substance information system of commercial professional associations)

SAFETY DATA SHEET (EC 1907/2006)

Lucitone 199, Liquid

Lucitone 199 Repair Material, Liquid

Lucitone FAS-POR, Liquid

Version: 3.12 / GB
Revision date: 13.11.2017
Issue date: 14.02.2003
replaces version: 3.11
Page: 5 / 12

Material no. 0D682007
Specification 142124
VA-Nr 01779070



The suitability for a specific workplace should be discussed with the producers of the protective gloves., The exact break through time can be obtained from the protective glove producer and this has to be observed.

Preventive skin protection, Use barrier cream regularly.

Eye/face protection

goggles

Skin and body protection

Immediately change moistened and saturated work clothes., Apply adequate skin protection agents before handling the product. Assure skin cleaning and skin care after work. Preventive skin protection is recommended.

Hygiene measures

Do not eat, drink, smoke, or sniff while at work. Wash your hands and/or face before breaks and before termination of work., If workplace exposure limits are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used., Avoid contact with skin and eyes., After contact with skin, wash immediately with plenty of water., If there is the possibility of skin/eye contact, the indicated hand/eye/body protection should be used.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form	liquid
Colour	colourless

Odour	ester-like
-------	------------

Odour threshold:	no data available
------------------	-------------------

pH	not applicable
----	----------------

Melting point/range	-48.2 °C tested substance: methyl methacrylate
---------------------	--

Boiling point/range	100.3 °C (1013 hPa) Method: DIN 51 751 tested substance: methyl methacrylate
---------------------	---

Flash point	10 °C Method: DIN 51 755 tested substance: methyl methacrylate
-------------	---

Evaporation rate	no data available
------------------	-------------------

Flammability (solid, gas)	no data available
---------------------------	-------------------

Lower explosion limit	2.1 %(V) tested substance: methyl methacrylate
-----------------------	--

Upper explosion limit	12.5 %(V) tested substance:
-----------------------	--------------------------------

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199, Liquid****Lucitone 199 Repair Material, Liquid****Lucitone FAS-POR, Liquid**

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **6 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**



	methyl methacrylate
Vapour pressure	38.7 hPa (20 °C) tested substance: methyl methacrylate
Density	0.94 g/cm ³ (20 °C) Method: DIN 51757 tested substance: methyl methacrylate
Water solubility	15.9 g/l (20 °C) tested substance: methyl methacrylate
Partition coefficient: n-octanol/water	POW: 1.38 tested substance: methyl methacrylate
Autoinflammability	Not capable of spontaneous combustion or heating.
Thermal decomposition	no data available
Viscosity, dynamic	0.63 mPa.s (20 °C) Method: Brookfield method tested substance: methyl methacrylate
Explosiveness	Vapours can form explosive mixtures with air.
Oxidizing properties	no data available

9.2. Other information

Ignition temperature	430 °C Method: DIN 51 794 tested substance: methyl methacrylate
Other information	No further physicochemical data were determined.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours may form explosive mixture with air.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Danger of bursting of closed systems to vigorous exothermic polymerization. Avoid uncontrolled polymerization.

10.4. Conditions to avoid

Avoid exposure to light /sunlight, Protect from heat sources of ignition.

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199, Liquid****Lucitone 199 Repair Material, Liquid****Lucitone FAS-POR, Liquid**

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **7 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**

**10.5. Incompatible materials**

Product polymerizes on contact with radical generating substances such as peroxides, azo compounds, heavy metal compounds, solutions.

10.6. Hazardous decomposition products

Heating can release vapours which can be ignited.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute oral toxicity	LD50 Rat: > 5000 mg/kg
	Method: OECD Test Guideline 401
	Test substance: methyl methacrylate literature
Acute inhalation toxicity	LC50 Rat: 29.8 mg/l / 4 h
	Test substance: methyl methacrylate (literature value)
Acute dermal toxicity	LD50 Rabbit: > 5000 mg/kg
	Test substance: methyl methacrylate literature
Skin irritation	irritating
	Test substance: methyl methacrylate literature
Eye irritation	slightly irritating
	Test substance: methyl methacrylate literature
Sensitization	May cause sensitisation by skin contact.
	Test substance: methyl methacrylate literature
Repeated dose toxicity	inhalative Rat
	Testing period: 2 Jahre
	NOAEL: 25 mg/kg
	target organ/effect: irritative effects, skin linings
	Test substance: methyl methacrylate literature
	Oral Rat
	Testing period: 2 Jahre
	NOAEL: 2000 mg/kg
	Test substance: methyl methacrylate
	drinking water analysis, no therapy-related results, literature
Assessment of STOT single exposure	no data available
Assessment of STOT repeat exposure	no data available
Risk of aspiration toxicity	no data available
Gentotoxicity in vitro	positive and negative

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199, Liquid****Lucitone 199 Repair Material, Liquid****Lucitone FAS-POR, Liquid**

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **8 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**



	Test substance: methyl methacrylate literature
Gentoxicity in vivo	no evidence of mutagenic effects Test substance: methyl methacrylate literature
Mutagenicity assessment	in vivo: no evidence of mutagenic effects
carcinogenicity assessment	no evidence that cancer may be caused, literature., tested substance:, methyl methacrylate
Toxicity to reproduction	no data available
teratogenicity assessment	no evidence of teratogenic properties, tested substance:, methyl methacrylate
Human experience	Frequent and continual skin contact can cause skin reaction (skin irritation, skin sensitization).

SECTION 12: Ecological information**12.1. Toxicity**

Toxicity to fish	LC50 <i>Lepomis macrochirus</i> : 191 mg/l / 96 h Test substance: methyl methacrylate literature Oncorhynchus mykiss: > 79 mg/l / 96 h Test substance: methyl methacrylate Method: OECD 203 literature
Toxicity in aquatic invertebrates	EC50 <i>Daphnia magna</i> : 68 mg/l / 48 h Test substance: methyl methacrylate Method: OECD 202 (literature value) EC50 <i>Daphnia magna</i> : 49 mg/l / 21 d Test substance: methyl methacrylate Method: OECD 202 part 2 (literature value)
Toxicity to algae	EC50 <i>selenastrum capricornutum</i> : 170 mg/l / 96 h Test substance: methyl methacrylate Method: OECD 201 literature
Toxicity to bacteria	EC0 <i>Pseudomonas putida</i> : 100 mg/l Test substance: methyl methacrylate literature

12.2. Persistence and degradability

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199, Liquid****Lucitone 199 Repair Material, Liquid****Lucitone FAS-POR, Liquid**

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **9 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**



Biodegradability

Exposure time: 14 Tage
Result: 94 % Readily biodegradable.
Test substance: methyl methacrylate
Method: OECD 301 C

12.3. Bioaccumulative potential

Bioaccumulation

Significant bioaccumulation need not be expected.

12.4. Mobility in soil

Mobility

If the product penetrates the soil it will become mobile and might pollute the groundwater.

12.5. Results of PBT and vPvB assessment

A PBT/vPvB evaluation is not available, since a chemical safety evaluation is not required / has not been carried out.

12.6. Other adverse effects

Further Information

Introduction into soil, natural water bodies or sewerage must be prevented.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Product**

Disposal according to local authority regulations.

Uncleaned packaging

Disposal according to local authority regulations.

SECTION 14: Transport information**Transport on land (ADR/RID/GGVSEB)**

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
ADR: Tunnel Restriction Code: (D/E)
ADR: Measures as 2.2.3.2.2 ADR/RID/ADN have been applied., Observe listed materials regulation §35, paragraph 1 GGVSEB
RID: Measures as 2.2.3.2.2 ADR/RID/ADN have been applied.

Inland waterway transport (ADN/GGVSEB (Germany))

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION
14.3. Transport hazard class(es): 3

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199, Liquid****Lucitone 199 Repair Material, Liquid****Lucitone FAS-POR, Liquid**

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **10 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**



- 14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
Measures as 2.2.3.2.2 ADR/RID/ADN have been applied.

Air transport ICAO-TI/IATA-DGR

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: Methyl methacrylate monomer, stabilized solution
14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
IATA-C: FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity-Regulation!
IATA-P: FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity-Regulation!

Sea transport IMDG-Code/GGVSee (Germany)

- 14.1. UN number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
14.5. Environmental hazards: --
14.6. Special precautions for user: Yes
EmS: F-E,S-D
Clear of living quarters., FOR USA ONLY: When shipping in, by or via USA note of the Reportable Quantity-Regulation!
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: for transportapproval see regulatory information

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National legislation**

employment restriction Note employment restrictions for pregnant and lactating women., Note employment restrictions for minors.

15.2. Chemical safety assessment

Chemical safety assessment No Chemical Safety Report as per Articles 2(8), 2(9) or 14 of the REACH Regulation is required for this product.

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199, Liquid****Lucitone 199 Repair Material, Liquid****Lucitone FAS-POR, Liquid**

Version: **3.12 / GB**
 Revision date: **13.11.2017**
 Issue date: **14.02.2003**
 replaces version: **3.11**
 Page: **11 / 12**

Material no. **0D682007**
 Specification **142124**
 VA-Nr **01779070**

**SECTION 16: Other information**

Classification and applied procedure to derive the classification of mixtures according to EU Regulation (EC) No. 1272/2008 (CLP)

Classification	Classification procedure
Flam. Liq., 2 , H225 Skin Corr./Skin Irrit., 2 , H315 Skin.sens., 1 , H317 STOT SE, 3 , H335	

Relevant H phrases from chapter 3

H225 : Highly flammable liquid and vapour.
 H315 : Causes skin irritation.
 H317 : May cause an allergic skin reaction.
 H335 : May cause respiratory irritation.

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Legend

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ASTM	American Society for Testing and Materials
ATP	Adaptation to Technical Progress
BCF	Bioconcentration factor
BetrSichV	German Ordinance on Industrial Safety and Health
c.c.	closed cup
CAS	Chemical Abstract Services
CESIO	European Committee of Organic Surfactants and their Intermediates
ChemG	German Chemicals Act
CMR	carcinogenic-mutagenic-toxic for reproduction
DIN	German Institute for Standardization
DMEL	Derived minimum effect level
DNEL	Derived no effect level
EINECS	European Inventory of Existing Commercial Chemical Substances
EC50	half maximal effective concentration
GefStoffV	German Ordinance on Hazardous Substances
GGVSEB	German ordinance for road, rail and inland waterway transportation of dangerous goods
GGVSee	German ordinance for sea transportation of dangerous goods
GLP	Good Laboratory Practice
GMO	Genetic Modified Organism
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization

SAFETY DATA SHEET (EC 1907/2006)**Lucitone 199, Liquid****Lucitone 199 Repair Material, Liquid****Lucitone FAS-POR, Liquid**

Version: **3.12 / GB**
Revision date: **13.11.2017**
Issue date: **14.02.2003**
replaces version: **3.11**
Page: **12 / 12**

Material no. **0D682007**
Specification **142124**
VA-Nr **01779070**



IMDG	International Maritime Dangerous Goods
ISO	International Organization For Standardization
LOAEL	Lowest observed adverse effect level
LOEL	Lowest observed effect level
NOAEL	No observed adverse effect level
NOEC	no observed effect concentration
NOEL	no observed effect level
o. c.	open cup
OECD	Organisation for Economic Cooperation and Development
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative, toxic
PEC	Predicted effect concentration
PNEC	Predicted no effect concentration
REACH	REACH registration
RID	Convention concerning International Carriage by Rail
STOT	Specific Target Organ Toxicity
SVHC	Substances of Very High Concern
TA	Technical Instructions
TPR	Third Party Representative (Art. 4)
TRGS	Technical Rules for Hazardous Substances
VCi	German chemical industry association
vPvB	very persistent, very bioaccumulative
VOC	volatile organic compounds
VwVwS	German Administrative Regulation on the Classification of Substances Hazardous to Waters into Water Hazard Classes
WGK	Water Hazard Class
WHO	World Health Organization