



Issue Date: 05/25/2015 Version No:

1. Identification

• Product identifier

Trade name: DHP Brand Bite Registration Material

HT102B Fast Set Unflavored HT103B Super Fast Unflavored 202B Fast Set Cool Mint

Application of the substance or the preparation

Addition curing vinyl polysiloxane dental impression materials (consisting of Base & Catalyst)

• Manufacturer/Supplier

Dental Health Products, Inc.

2614 North Sugar Bush Road New Frankin, WI 54229-0176 USA

Tel: 920-866-9001 800-626-2163 Fax: 920-866-1865 E-mail: info@dhpi.net

24HR Emergency Telephone numbers

CHEMTREC (800) 424-9300

2. Hazards Identifications

The preparation of this document has been carried out according to the U.S. OSHA Hazard Communication Standard. Therefore, all the known hazards of the product or components has to be included regardless the potential risk.

Hazard classification

Skin sensitizer: Category 1

Label elements

Signal word: Warning. Symbols: Exclamation mark. Pictograms



Hazard statement

May cause an allergic skin reaction. Causes severe eye irritation.

• Precautionary statements Prevention:

Wear protective gloves, protective clothing and eye protection.

Work clothing which is contaminated must not be allowed out of workplace.

Wash thoroughly after handling.



Issue Date: 05/25/2015 Version No:

1

Response:

IF ON SKIN: Wash with plenty of water and soap. In case skin irritation occurs, seek medical attention. Contaminated clothing must be washed before reuse.

IF IN EYES: Rinse with caution with plenty of water for several minutes. In case contact lenses are worn remove and continue rinsing. If you feel unwell get medical attention.

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Classification system

NFPA ratings (scale 0 – 4)



Health = 2Fire = 0Reactivity = 0



HMIS ratings (scale 0 - 4)

Health = *2

0

Reactivity = 0

• Hazards not otherwise classified None.

3. Composition/Information on ingredients

• Chemical characterization

Mixture of addition-curing silicones.

C.A.S. No.	Component	% Wt
68083-19-2	Polydimethylsiloxane vinyl terminated	20 - 40
68037-59-2	Dimethylsiloxane copolymer	1 - 10
14808-60-7	Quartz silica	30 - 50
27306-78-1	Polysiloxane	< 5

4. First aid measures

Description of first aid measures

After inhalation

Remove person to fresh air. Get medical attention if you feel unwell.

After contact with skin

Immediately flush with water and then wash with soap and water. In case skin irritation persists, get medical attention.

After contact with eyes

Rinse with copious amounts of water for at least 15 minutes. Get medical attention.





Issue Date: 05/25/2015 Version No:

1

After ingestion

Flush mouth with water and get medical attention.

• Further information None

5. Fire-fighting measures

• Suitable extinguishing media

Water spray, foam, carbon dioxide, dry chemicals depending on the materials involved in the fire.

- Extinguishing media to avoid Not known.
- Special hazards arising from combustion

No relevant information is available for this product.

• Special protective equipment for fire-fighters No special measures are required.

6. Accidental release measures

• Personal precautions, protective equipment and emergency procedures

Ventilate area. Avoid contact with skin and eyes.

Environmental precautions

Do not allow to enter sewers or ground water

• Methods for cleaning up/collecting

Collect mechanically. The product may be absorbed by liquid-binding material (sand, diatomite, acid binders).

7. Handling and storage

· Precautions for safe handling

Adequately trained personnel should handle this product. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Contaminated clothing should not be allowed out of the workplace and in any case it should be washed before reuse. Keep container tightly closed.

Precautions in case of fire and explosion

Extinguish all sources of ignition. No special measures required.

• Conditions for safe storage, including any incompatibilities

Store product in a cool and dry place. Avoid direct sunlight, strong bases, acids, oxidizing agents and amines. Store in the original container.



Page 4 of 9

DHP BRAND BITE REGISTRATION SAFETY DATA SHEET

Issue Date: 05/25/2015 Version No:

Exposure controls/personal protection

Control parameters

Occupational exposure limits



Issue Date: 05/25/2015 Version No:

1

In case a component is shown in section 3 but it does not appear in the table below, there are not any available data for this component.

C.A.S. No.	Component	Agency	Limit
14808-60-7	Quartz silica	ACGIH	TWA: 0.025* mg/m ³ * respirable fraction
14808-60-7	Quartz silica	OSHA	TWA: 0.3* mg/m³ * concentration as a total of dust TWA: 0.1* mg/m³ (2.4 millions of particles/cu. ft.) * concentration respirable

ACGIH: American Conference of Government Industrial Hygienists

OSHA: United States Department of Labour – Occupational Safety and Health Administration TWA: Time-Weighted-Average

Exposure control

Personal protective equipment (PPE)

Ventilation: Ensure adequate ventilation of the premises where the product is stored and/or handled.

Respiratory protection: Not required.

Hand protection: Suitable protective gloves may be worn. The use of vinyl gloves is suggested.

(Setting time of polyvinylsiloxanes is inhibited by latex gloves).

Eye protection: Safety goggles are recommended.

Skin protection: Do not eat, drink or smoke when using the product.

Other: Lab coat is suggested when using the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance: Bicomponent pastes/viscous liquids

Colour: Different Odour: Characteristic Odour threshold: Not available pH value Not applicable Melting point: Not applicable Boiling point: Not applicable Not applicable Flash point: Evaporation rate: No data available Flammability (solid, gas): Not applicable Density: $1,2-1,8 \text{ g/cm}^3$ Vapour pressure: Not applicable Not applicable Vapour density: Viscosity: Not determined Solubility: Insoluble in water

Auto ignition: Product is not self igniting

Flash point: No flash point





Issue Date: 05/25/2015 Version No:

1

Boiling point: Not applicable Viscosity: No data available

10. Stability and reactivity

Reactivity

No relevant information available.

· Chemical stability

Stable under normal storage and handle conditions.

Hazardous decomposition products

None, if used in accordance with instructions.

· Conditions to avoid

No relevant information available, if used in accordance with instructions.

• Possibility of hazardous reactions

None, if used in accordance with instructions

11. Toxicological information

It is required by the U.S. OSHA Hazard Communication Standard to include all the known hazards of the product or components included regardless the potential risk.

All the information presented below corresponds to the uncured components included in the product. Once the product is mixed according to the instructions for use it is safe for its intended use.

Information on toxicological effects

Inhalation: No adverse health effects are expected.

Skin contact: May cause mild irritation.

Eye contact: May cause irritation.

Ingestion: There is a possibility of gastrointestinal irritation with the symptoms being stomach pain and upset, nausea, diarrhoea and vomiting.

• Additional toxicological information Carcinogenicity:

During normal / intended use it is not expected to cause the following health effect(s) during exposure

C.A.S. No.	Component	Class description	Regulation
14808-60-7	Quartz silica	Group 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological data:

In case a component is shown in section 3 but it does not appear in the table below, there is not any available data for this component. **Acute toxicity**

Component	Route	Species	Value
Polydimethylsiloxane vinyl terminated	Dermal	Rabbit	LD50 > 15,440 mg/Kg



Version No: Issue Date: 05/25/2015

	Ingestion	Rat	LD50 > 15,440 mg/Kg
	Dermal	Rabbit	LD50 > 2,000 mg/Kg
Dimethylsiloxane copolymer	Ingestion	Rat	LD50 > 2,000 mg/Kg
	Inhalation	Rat	LC50 4.2 mg/l
Occard a silica	Dermal		LD50 > 5,000 mg/Kg
Quartz silica	Ingestion		LD50 > 5,000 mg/Kg
	Dermal	Rabbit	LD50 > 2,000 mg/Kg
Polysiloxane	Ingestion	Rat	LD50 > 2,000 mg/Kg
	Inhalation	Rat	LC50 2 mg/l

Skin corrosion/irritation

Component	Species	Value
Polydimethylsiloxane vinyl terminated	Rabbit	Mild irritation
Quartz silica		No significant irritation
Polysiloxane	Rabbit	No significant irritation

Serious eye damage/Irritation

Component	Species	Value
Polydimethylsiloxane vinyl terminated	Rabbit	Mild irritation
Polysiloxane	Rabbit	Severe irritation

Skin sensitization

Component	Species	Value
Polysiloxane	Guinea pig	Not sensitizing

Respiratory sensitization:

In case a component is shown in section 3 but it does not appear in the table below, there is not any available data for this component.

Germ cell mutagenicity

Component	Route	Value
Polysiloxane	In vitro	Not mutagenic
Quartz silica	In vitro	Not mutagenic

Carcinogenicity

Component	Route	Species	Value
Quartz silica	Inhalation	Human and Animal	Carcinogenic

Reproduced toxicity:

In case a component is shown in section 3 but it does not appear in the table below, there is not any available data for this component.

Reproduced and/or development effects

Component	Route	Value	Species	Test Result	Exposure duration
-----------	-------	-------	---------	--------------------	--------------------------



Issue Date: 05/25/2015 Version No:

1

Polysiloxane	Ingestion	There is evidence for	Rat	NOAEL	pre-mating &
		positive reproduction but limited data for		450 mg/Kg/day	during gestation
		classification			

Target organ(s):

In case a component is shown in section 3 but it does not appear in the table below, there is not any available data for this component.

Specific target organ toxicity - single exposure

In case a component is shown in section 3 but it does not appear here, there is not any available data for this component

Specific target organ toxicity - repeated exposure

Component	Route	Target organ	Value	Species	Test Result	Exposure duration
Quartz silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	Occupation al exposure

Aspiration hazard:

In case a component is shown in section 3 but it does not appear here, there is not any available data for this component.

12. Ecological information

If material is properly used and handled no ecological problems are to be anticipated Do not discard material into drains/sewers or aquatic environment

13. Disposal considerations

Disposal must be carried out in accordance to the local and national regulations currently in force

14. Transport information

UN-Number
DOT, ADR, ADN, IMDG, IATA
UN proper shipping name
DOT, ADR, ADN, IMDG, IATA
Transport hazard class
DOT, ADR, ADN, IMDG, IATA
Class
Packing group
None
DOT, ADR, IMDG, IATA



Page 9 of 9

DHP BRAND BITE REGISTRATION SAFETY DATA SHEET

Issue Date: 05/25/2015 Version No:

1

15. Regulatory information

The product is not considered hazardous under D. Lgs. 65/03.

The product is a medical device according to EC directive 93/42/EEC

This product is classified as a medical device under US regulations and it has been reviewed by the US Food and Drug Administration (FDA)

16. Other information

CAUTION: PRODUCT FOR PROFESIONAL USE ONLY

The information provided above is based on our present knowledge and experience. This safety data sheet refers explicitly to the product indicated and comprises no guarantee of particular quality. Any use of this product in any way not indicated on this safety data sheet will be exclusively under the user's responsibility