

SAFETY DATA SHEET

Section 1. Product And Company Identification

Product Name: Tubli-Seal™ EWT Accelerator and Tubli-Seal™ EWT Accelerator Express

Product Use: Dental product: Endodontic Obturation Systems and Fill Products

Manufacturer: Kerr Corporation

1717 W. Collins Ave. Orange, CA 92867-5422

U.S.A.

Information Phone Number: 1-800-841-1428 (Customer Service)

Chemical Emergency Phone Number (Chemical Spills, Leaks, Fire, Exposure or Accident only):

CHEMTREC 1-800-424-9300 (in the US) 1-703-527-3887 (Outside the US)

SDS Date of Preparation/Revision: May 21, 2019

Section 2. Hazards Identification

GHS Classification:

Eye Irritation Category 2A Skin Sensitization Category 1

Label Elements:

Warning!



Hazard Phrases

Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary Phrases:

Avoid breathing dust, fumes, gas, mist, vapors, spray.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves, eye protection.

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or a rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Dispose of contents and container in accordance with local and national regulations.



Section 3. Composition/Information on Ingredients

Component	CAS No.	Amount
Eugenol	97-53-0	10-30%
White mineral oil (petroleum)	8042-47-5	5-10%

Section 4. First Aid Measures

Inhalation: Remove victim to fresh air. Get immediate medical attention if symptoms occur.

Skin Contact: Flush thoroughly with water. Get medical attention if irritation or symptoms of exposure develop. Remove and launder contaminated clothing before re-use.

Eye Contact: Rinse thoroughly with water. Get medical attention if irritation occurs and persists.

Ingestion: Do NOT induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. Keep the victim calm and warm. Get immediate medical attention.

Most important symptoms and effects, acute and delayed: Causes serious eye irritation and may cause skin dryness and irritation. Ingestion may be irritating to mouth, throat and stomach.

Indication of immediate medical attention and special treatment, if needed: Immediate medical attention is not required.

Section 5. Fire Fighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use any media appropriate for the surrounding fire. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Combustion may produce carbon dioxide and carbon monoxide.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored. Cool fire-exposed containers with water. Contain water used in firefighting from entering sewers or natural waterways.

Section 6: Accidental Release Measures

Personal precautions, Protective equipment, and Emergency procedures: Evacuate spill area and keep unprotected personnel away. Avoid contact with eyes, skin and clothing. Wear appropriate protective clothing and equipment. Do not breathe dust or vapors.

Environmental Precautions: Avoid releases to the environment. Report spill as required by local and federal regulations.

Methods and Materials for Containment and Cleaning up: Prompt cleanup and removal are necessary. Absorb spills with an inert material and place in an appropriate waste disposal container.



Section 7. Handling and Storage

Precautions for Safe Handling: Prevent contact with eyes, skin and clothing. Always wear impervious gloves, chemical safety goggles and protective clothing when handling this material. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke in the work area. Use with adequate ventilation. Remove and wash contaminated clothing before reuse.

Empty containers retain product residues which can be hazardous. Follow all SDS precautions when handling empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, well-ventilated area away from direct sunlight. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

Section 8. Exposure Controls / Personal Protection

Exposure Limits

Chemical	Exposure Limit		
Eugenol	None Established		
White mineral oil (petroleum)	5 mg/m³ TWA ACGIH TLV (inhalable		
	fraction)		

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

Respiratory Protection: None under normal use conditions with adequate ventilation. For operations where the occupational exposure limits are exceeded, an approved respirator with particulate cartridges is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with applicable regulations and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Hand protection: Impervious gloves are suggested to prevent skin contact. Contact your glove supplier for selection assistance.

Eye Protection: Chemical safety goggles are recommended if contact is possible.

Skin Protection: Wear protective clothing as needed to avoid skin contact and contamination of personal clothing.

Hygiene measures: Suitable eye and skin washing facilities should be available in the work area.

Section 9. Physical and Chemical Properties

Point/Range:

Appearance:Amber pasteOdor:AromaticOdor Threshold:Not availablepH:Not availableMelting/FreezingNot availableBoilingNot available

Point:

Flash Point: Not flammable Evaporation Not available



Rate:

Flammability: (Solid,

Gas)

Vapor Pressure:

Relative Density: Partition Coefficient:

(N-Octanol/Water)

Not applicable

Not available

Not available

Flammability Limits:

LEL: Not applicable **UEL**: Not applicable

Not available

Vapor Density:

Solubilities: Autoianition

Insoluble in water Not available

Temperature:

Not available

Viscosity:

>20.5 mm²/s (kinematic)

Decomposition Temperature:

Section 10. Stability and Reactivity

Reactivity: The product is not expected to be reactive.

Chemical Stability: Stable under normal storage and handling conditions. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to avoid: Avoid excessive heat.

Incompatible Materials: Oxidizing materials, acids and alkalis. Hazardous decomposition products: None if stored normally.

Section 11. Toxicological Information

Potential Health Effects:

Inhalation: None known.

Skin Contact: May cause skin dryness and irritation.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion may be irritating to mouth, throat and stomach.

Chronic Hazards: Prolonged or repeated contact can defat the skin and lead to irritation, cracking

and/or dermatitis.

Skin Sensitization: No adverse effects expected. This product is classified as Grade I – weak sensitizer

in Kligman test.

Respiratory Sensitization: No data available. This product is not expected to cause respiratory

sensitization.

Germ Cell Mutagenicity: None of the components are mutagenic.

Carcinogen: None of the components are listed as a carcinogen or potential carcinogen by IARC, NTP,

ACGIH, or OSHA.

Developmental / Reproductive Toxicity: None of the components have been shown to cause

reproductive or developmental toxicity.

Specific Target Organ Toxicity (Single Exposure): No data available.

Specific Target Organ Toxicity (Repeated Exposure): No data available.

Aspiration Toxicity: White mineral oil (petroleum) is classified as an aspiration hazard category 1.



Acute Toxicity Values:

Product ATE: 7942.4 mg/kg (Oral) Eugenol: LD50 Oral rat: 1930 mg/kg

White mineral oil (petroleum): LD50 Oral rat: >5000 mg/kg; LD50 Dermal rabbit: >2000 mg/kg;

LC50 Inhalation rat: >5000 mg/L/4hr

Section 12. Ecological Information

Toxicity:

Eugenol: 96 hr LC50 Pimephales promelas 24 mg/L

White mineral oil (petroleum): 96 hr LC50 Lepomis macrochirus >10 g/L

This product is classified as harmful to the aquatic environment. Releases to the environment should be avoided.

Persistence and degradability: Eugenol is readily biodegradable.

Bioaccumulative Potential:

Eugenol has a BCF of 2.27, potential for bioaccumulative is low.

White mineral oil (petroleum): log P_{ow} >6, potential for bioaccumulative is high.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

Section 13. Disposal Considerations

Disposal: For unused solution, flush thoroughly with large quantities if water into sewage disposal system in accordance with Federal, State, and local regulations. For used solution, the waste solution must be characterized by the generator and disposed of in accordance with Federal, State, and local regulations.

Container Disposal: Rinse empty container thoroughly with water and discard clean, empty container as general trash or offer for recycling, if available.

Section 14. Transport Information

	UN Number	UN Proper Shipping Name	Hazard	Packing	Environmental
			Class(s)	Group	Hazards
US DOT	None	Not Regulated	None	None	None
Canada	None	Not Regulated	None	None	None
TDG					
IMDG	None	Not Regulated	None	None	None
IATA/ICAO	None	Not Regulated	None	None	None

Section 15. Regulatory Information

U.S. Federal Regulations:

EPA SARA 311/312 Hazard Classification: Refer to Section 2 for OSHA Hazard Classification.



EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None.

Protection Of Stratospheric Ozone: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: This product is not subject to CERCLA reporting requirements; however, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

US EPA TSCA Inventory: All of the components of this product are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory or exempt.

Canadian Regulations:

Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL) or exempt.

National Pollutant Release Inventory (NPRI): This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements NPRI: None

International Inventories

Australia: All of the components in this product are listed on the Australian Inventory of Chemical Substances (AICS) or exempt.

China: All of the components in this product are listed on the Inventory of Existing Chemical Substances in China (IECSC) or exempt.

European Union: All the components in this product are listed on the EINECS inventory or exempt.

Korea: All of the components in this product are listed on the Korean Existing Chemicals List (KECL) or exempt.

New Zealand: All of the components in this product are listed on the New Zealand Inventory of Chemicals (NZIoC) or exempt.

Section 16. Other Information

NFPA Rating: Fire: 0 Health: 2 Instability: 0

Effective Date: May 21, 2019 Supersedes Date: October 21, 2014

Revision Summary: All Sections – New SDS format

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date of preparation, however, KERR Corporation makes no warranty with respect to the accuracy or suitability of the recommendations, and assumes no liability to any use thereof.