

SAFETY DATA SHEET

ESTELITE COLOR

1. Identification

Product identifier

Product name ESTELITE COLOR

Recommended use of the chemical and restrictions on use

Application Light-cured Characterizing Material. For dental professionals only.

Details of the supplier of the safety data sheet

Supplier Tokuyama Dental America, Inc.
740 Garden View CT., Suite 200 Encinitas,
CA 92024 U.S.A.
Tel: (877) 378 3548 (Toll-Free)
Tel: (760)942-7211
Fax: (760)942-7212

Contact Person <http://www.tokuyama-dental.com/tdc/contact.html>

Manufacturer Tokuyama Dental Corporation
38-9, Taitou 1-chome, Taitou-ku, Tokyo
110-0016, Japan
TEL: +81-3-3835-2261
FAX: +81-3-3835-2265

Emergency telephone number

Emergency telephone California Poison Control System - San Francisco Division
San Francisco General Hospital
Bldg 5 Rm 2A21, 1001 Potrero Ave, San Francisco
Emergency telephone number: 1 800 222 1222
E-mail address: coadmin@calpoison.org
<http://www.calpoison.org>

National Capital Poison Center
3201 New Mexico Ave, Ste 310, Washington DC
Emergency telephone number: 1 800 222 1222
Telephone number: +1 202 362 3867
Facsimile number: +1 202 362 8377
E-mail address: pc@poison.org
<http://www.poison.org>

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 : Eye Irrit. 2A - H319 : Skin Sens. 1 - H317 : STOT SE 3 - H335

Environmental hazards Not Classified

Label elements

ESTELITE COLOR**Pictogram****Signal word**

Warning

Hazard statements

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

Precautionary statements

P261 Avoid breathing dust.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a poison center/ doctor if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with local regulations.

Contains

BISPHENOL A POLYETHOXY DIMETHACRYLATE, TRIETHYLENE GLYCOL DIMETHACRYLATE, 2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] ESTER

3. Composition/information on ingredients**Mixtures**

BISPHENOL A POLYETHOXY DIMETHACRYLATE	10-30%
--	---------------

CAS number: 41637-38-1

TRIETHYLENE GLYCOL DIMETHACRYLATE	5-10%
--	--------------

CAS number: 109-16-0

2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] ESTER	<1%
--	---------------

CAS number: 1565-94-2

TITANIUM DIOXIDE	<0.1%
-------------------------	-----------------

CAS number: 13463-67-7

ESTELITE COLOR

p-METHOXYPHENOL	<1%
CAS number: 150-76-5	

2,6-DI-tert-BUTYL-p-CRESOL	<1%
CAS number: 128-37-0	
M factor (Chronic) = 1	

4. First-aid measures

Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Try to induce vomiting. Get medical attention if any discomfort continues.
Skin Contact	Wash skin thoroughly with soap and water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

Inhalation	May cause respiratory irritation.
Skin contact	Skin irritation. Allergic rash.
Eye contact	May cause severe eye irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Special hazards arising from the substance or mixture

Specific hazards	In case of fire, toxic gases may be formed.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors.
---	---------------------------------------

Special protective equipment for firefighters	Wear chemical protective suit.
--	--------------------------------

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses.
----------------------------------	---

ESTELITE COLOR

Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Collect and place in suitable waste disposal containers and seal securely.

Reference to other sections For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet. All handling should only take place in well-ventilated areas. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Avoid breathing vapour/spray.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Take off contaminated clothing and wash it before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Store at temperatures between 0°C/32°F and 25°C/77°F. Keep away from heat, sparks and open flame. Protect from light.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

A4, A4, A4

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

p-METHOXYPHENOL

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

2,6-DI-tert-BUTYL-p-CRESOL

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

A4, A4, A4

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

OSHA = Occupational Safety and Health Administration.

Exposure controls

Appropriate engineering controls Provide adequate general and local exhaust ventilation.

ESTELITE COLOR

Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Wear protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Take off contaminated clothing and wash it before reuse.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Paste
Color	Blue, Gray, Lavender, Ochre, Yellow, Red, Pink, White, Yellow white, Dark brown, Clear
Odor	Characteristic
Odor threshold	Not available.
pH	Technical impossibility to obtain the data.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not applicable.
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.7
Solubility(ies)	Not available.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidizing properties	Not available.
Other information	Not available.

ESTELITE COLOR

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Not known.
Conditions to avoid	Keep away from heat, sparks and open flame. Protect against direct sunlight.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Heating may generate the following products: Toxic gases or vapors.

11. Toxicological information

Information on toxicological effects

Toxicological effects No data on possible toxic effects have been found.

Acute toxicity - oral

Notes (oral LD₅₀) Not available.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not available.

Skin corrosion/irritation

Skin corrosion/irritation Skin Irrit. 2 - H315, Causes skin irritation.

Animal data

Not available.

Serious eye damage/irritation

Serious eye damage/irritation Eye Irrit. 2 - H319 Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Not available.

Skin sensitization

Skin sensitization Skin Sens. 1 - H317 May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Genotoxicity - in vivo

Not available.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Some of the ingredients are listed or exempt.

OSHA Carcinogenicity

Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

ESTELITE COLOR

Reproductive toxicity - development Not available.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Not available.

Toxicological information on ingredients.

TITANIUM DIOXIDE

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 1.5

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

2,6-DI-tert-BUTYL-p-CRESOL

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Toxicity No data available.

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility No information available.

Other adverse effects

ESTELITE COLOR

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

Not applicable.

UN No. (IMDG) N/A

UN No. (ICAO) N/A

UN No. (DOT) N/A

UN proper shipping name

Not applicable.

Transport hazard class(es)

Not applicable.

IMDG Class Not applicable.

ICAO class/division Not applicable.

Transport labels

No transport warning sign required.

Packing group

Not applicable.

IMDG packing group Not applicable.

ICAO packing group Not applicable.

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Regulatory References 29 CFR 1910. 1200(g) Federal Regulations (OSHA Standard).

US Federal Regulations

ESTELITE COLOR

SARA (311/312) Hazard Categories

Acute

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

TITANIUM DIOXIDE

California Directors List of Hazardous Substances

p-METHOXYPHENOL

2,6-DI-tert-BUTYL-p-CRESOL

Massachusetts "Right To Know" List

TITANIUM DIOXIDE

p-METHOXYPHENOL

2,6-DI-tert-BUTYL-p-CRESOL

Rhode Island "Right To Know" List

TITANIUM DIOXIDE

p-METHOXYPHENOL

2,6-DI-tert-BUTYL-p-CRESOL

Minnesota "Right To Know" List

TITANIUM DIOXIDE

p-METHOXYPHENOL

2,6-DI-tert-BUTYL-p-CRESOL

New Jersey "Right To Know" List

TITANIUM DIOXIDE

p-METHOXYPHENOL

2,6-DI-tert-BUTYL-p-CRESOL

Pennsylvania "Right To Know" List

TITANIUM DIOXIDE

p-METHOXYPHENOL

2,6-DI-tert-BUTYL-p-CRESOL

16. Other information

Training advice	Ensure operatives are trained to minimize exposure. Only trained personnel should use this material.
Revision comments	Revised formulation.
Revision date	7/20/2017
Revision	2

ESTELITE COLOR

Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
----------------------------------	--

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.