

Page 1/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/12/2015

Tel.: 0800 4372522

1 Identification

- · Product identifier
 - · Trade name: Signum connector
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Auxiliary for manufacture of dental prothesis
- · Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Heraeus Kulzer GmbH

Grüner Weg 11, D-63450 Hanau

· Information department:

Marc Henn

Tel. +1 (574) 2995444 / Fax: +1 (574) 2912542

e-mail: marc.henn@kulzer-dental.com

• Emergency telephone number:

Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· Classification of the substance or mixture

H225 Highly flammable liquid and vapor. Flam. Liq. 2

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation. STOT SE 3

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS05 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

methyl methacrylate

Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxid

Hazard statements

Highly flammable liquid and vapor.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

(Contd. on page 2)



Page 2/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015 Reviewed on 05/12/2015

Trade name: Signum connector

(Contd. of page 1)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system

· NFPA ratings for USA (scale 0-4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-Ratings (Scale 0-4)



Health = *1 Fire = 3 Reactivity = 0

- · Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description: Composition based on methacrylates

· Dangerous components:	
80-62-6 methyl methacrylate	50-75%
75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxid	0-5%

4 First-aid measures

- · Description of first aid measures
 - After inhalation Supply fresh air; consult doctor in case of complaints.
 - · After skin contact immediately wash with water and soap and rinse thoroughly.
 - · After eye contact
 - Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
 - · After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
 - · For safety reasons unsuitable extinguishing agents Water.

Water with full jet.

· Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
 - · Protective equipment: No special measures required.

(Contd. on page 3)



Page 3/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015 Reviewed on 05/12/2015

Trade name: Signum connector

· Additional information -

(Contd. of page 2)

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- · Methods and material for containment and cleaning up:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).

Reference to other sections

No dangerous substances are released.

See Section 8 for information on personal protection equipment.

7 Handling and storage

· Precautions for safe handling

Wear protective equipment. Keep unprotected persons away.

Keep receptacles tightly sealed.

Please observe the additional instructions in the product's instructions for use.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
 - - Requirements to be met by storerooms and receptacles: Store in a cool location.
 - · Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions:

Keep cool, if possible (not above 25 °C). Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

PEL 410 mg/m³, 100 ppm

REL 410 mg/m³, 100 ppm

Short-term value: 410 mg/m³, 100 ppm

Long-term value: 205 mg/m³, 50 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls
 - Personal protective equipment
 - General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 4)



Page 4/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015 Reviewed on 05/12/2015

Trade name: Signum connector

(Contd. of page 3)

Breathing equipment:

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· Protection of hands:

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Wear protective gloves based on polyvinyl alcohole.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Chloroprene rubber, CR

- · Eye protection: Not absolutely necessary.
- · Body protection: Light weight protective clothing

9 Physical and chemical properties

 Information on basic physical and General Information 	cnemical properties
· Appearance:	
· Form:	Fluid
· Color:	Colorless
· Odor:	Ester-like
Change in condition Melting point/Melting range: Boiling point/Boiling range:	undetermined 100 °C (212 °F)
· Flash point:	10 °C (50 °F)
· Ignition temperature:	430.0 °C (806 °F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
· Explosion limits:	
· Lower:	2.1 Vol %
· Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	· 47 hPa (35 mm Ha)

(Contd. on page 5)



Page 5/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015 Reviewed on 05/12/2015

Trade name: Signum connector

(Contd. of page 4) · Density at 20 °C (68 °F): 1.000 g/cm3 (8.345 lbs/gal) · Solubility in / Miscibility with Not miscible or difficult to mix · Water: · Solvent content: 8.0 % · Solids content: No further relevant information available. Other information

10 Stability and reactivity

- Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: none
 - Additional information:

Product might polymerize after considerable exceeding of recommended storage time or temperature.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· LD/	· LD/LC50 values that are relevant for classification:				
80-62-6 m	80-62-6 methyl methacrylate				
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>5000 mg/kg (rab)			
Inhalative	LC50/4 h	29.8 mg/l (rat)			

- · Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
 Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

· Carcinogenic categories

	· IARC (International Agency for Research on Cancer)
ı	80-62-6 methyl methacrylate 3
	Butyl-hydroxy-toluol 3
Ī	· NTP (National Toxicology Program)
	None of the ingredients is listed.
	· OSHA-Ca (Occupational Safety & Health Administration)
	None of the ingredients is listed.

12 Ecological information

- · Toxicity
 - · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 6)



Page 6/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015 Reviewed on 05/12/2015

Trade name: Signum connector

(Contd. of page 5)

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
 - · Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT	UN1247
· ADR, IMDG, IATA	1247
· UN proper shipping name · DOT, IMDG, IATA	METHYL METHACRYLATE MONOMER STABILIZED, solution
· ADR	1247 METHYL METHACRYLATE MONOME STABILIZED, solution
· Transport hazard class(es)	
· DOT	
*	
· Class · Label	3 Flammable liquids 3
· ADR	
**	
· Class · Label	3 (F1) Flammable liquids 3

(Contd. on page 7)



Page 7/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015 Reviewed on 05/12/2015

Trade name: Signum connector

(Contd. of page 6)

· IMDG, IATA



· Class 3 Flammable liquids · Label

· Packing group · DOT, ADR, IMDG, IATA II

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 339 · EMS Number: F-E,S-D

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· UN "Model Regulation": UN1247, Methyl methacrylate monomer, stabilized,

solution, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· Cancerogenity categories

· TLV (Threshold Limit Value established by ACGIH)

80-62-6 methyl methacrylate A4 Butyl-hydroxy-toluol A4

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









· Signal word Danger

· Hazard-determining components of labeling:

methyl methacrylate

Diphényl(2,4,6-trimethylbenzoyl)phosphinoxid

Hazard statements

Highly flammable liquid and vapor.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

(Contd. on page 8)



Page 8/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/12/2015

Trade name: Signum connector

(Contd. of page 7)

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 05/12/2015 /

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
ELINCS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

LD50: Letnal dose, ou percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* Data compared to the previous version altered.