DentsplySirona Safety Data Sheet



1. Identification

Product Name	SDS Code Number
Self Cure Activator	534891
Trade Name & Synonyms	Date of Last Revision
Self Cure Activator	11/18/19
Manufacturer:	Address
DENTSPLY Milford	38 West Clarke Avenue
	Milford DE 19963-1805
	http://www.dentsplysirona.com
Grades or Minor Variant Identities	Company Telephone Number (Product Inquiries) (302) 422-4511
Not Applicable	(8:00 AM – 4:30 PM Eastern Time)
Product Use (for Canada)	Emergency Telephone Number
Not Applicable	CHEMTREC: 1-800-424-9300 (24 hours)
	(Outside U.S. +1-703-527-3887) CCN6510

2. Hazard(s) Identification



DANGER HIGHLY FLAMMABLE LIQUID AND VAPOR



MAY CAUSES AN ALLERGIC SKIN REACTION

Keep away from heat/sparks/open flames / hot surfaces. No smoking.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

In case of fire: Use dry chemical, alcohol foam, or carbon dioxide for extinction.

Store in a well ventilated place. Keep Cool.

Avoid breathing vapors.

Contaminated work clothing should not be allowed out of the workplace.

Wash thoroughly after handling.

Wear protective gloves.

IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical attention.

IF ON SKIN: Remove immediately all contaminated clothing. Rinse with water.

If skin irritation occurs: Get Medical Advice/attention.

Wash contaminated clothing before reuse.

Avoid breathing vapors.

Use only outdoors or in well ventilated area.

IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON Center or physician if you feel unwell.

Dispose of contents/container in accordance with local regulations.

3. Composition/Information on Ingredients

Hazardous Components	C.A.S. Number	Exposure Limits	%
Acetone	67-64-1	500 ppm	< 70
Urethane dimethacrylate resin	105883-40-7	Not Applicable	< 20
2-Hydroxyethyl methacrylate	868-77-9	Not Applicable	< 10
Initiator	Trade Secret	Not Applicable	< 5

4. First Aid Measures

Routes of Exposure	First Aid Instructions	Immediate Medical Attention	Delayed Effects
Eye	Rinse opened eye for several minutes under running water. If symptoms persist	Not Applicable	Not Applicable
	consult physician		

Skin	Immediately wash with soap and water and rinse thoroughly	Not Applicable	Not Applicable	
Inhalation	Supply fresh air.	Not Applicable	Not Applicable	
	This may not be of concern when using clinically relevant quantities.			
Ingestion	This may not be of concern when using clinically relevant quantities.	Not Applicable	Not Applicable	
Other Not Applicable Not Applicable Not Applicable				
Note to Physicians (Treating Testing and Monitoring). Treat symptomatically				

5. Fire Fighting Measures

Flashpoint Method: 2°C (36°F)	Flammable (Explosive) Limits in Air	Autoignition Temperature: Not	Other: Not		
Pensky-Marten Closed Cup	LEL: 2.5 vol. % UEL: 12. 8 vol. %	Applicable	Applicable		
Flame Propagation or Burning Rate (for Solids): Not	Properties Contributing to Fire	Flammability Classification: 3			
Applicable	Intensity: Not Applicable				
Extinguishing Media: CO ₂ , extinguishing powder or water spray. Fight larger fires with water Extinguishing Media to Avoid:					
sprat or alcohol resistant foam. Water with full jet.					
Protection and Procedures for Firefighters: Firefighters should wear self-contained respiratory protective devices.					
Unusual Fire and Explosion Hazards: Formation of toxic gases is possible during heating or in case of fire.					

6. Accidental Release Measures

Containment Techniques: Wear protective clothing and absorb spill with inert material (e.g. vermiculite, sand, earth), then place material in suitable labeled plastic or metal container.

Spill/Leak Clean-up Procedures and Equipment: Wear protective clothing and absorb spill with inert material (e.g. vermiculite, sand, earth), then place material in suitable labeled plastic or metal container. Avoid gross skin contact to minimize the possibility of contact dermatitis to susceptible

persons. Ensure adequate ventilation.

Evacuation Procedures: Not Applicable | Special Instructions: Not Applicable | Reporting Requirements: Not Applicable

7. Handling and Storage

Handling Practices and Warnings: Handling of this product should be by trained dental healthcare professionals only. Observe normal care for working with chemicals.

Storage Practices and Warnings: Store only in the original package. Keep package tightly sealed. Protect from exposure to direct light. Store away from food and beverages.

8. Exposure Control / Personal Protection









Ventilation: None required during normal intended use of this product				
Engineering Controls: Not Applicable				
Personal Protective Equipment for Normal Use	Personal Protective			
	Equipment for Emergencies			
Safety Glasses	Not Applicable			
The glove material has to be impermeable and resistant to the product.	Not Applicable			
Not required when using clinically relevant quantities used in Dental office.	Not Applicable			
Body Protection Protective work clothing Not Applicable				
	Not Applicable Personal Protective Equipment for Normal Use Safety Glasses The glove material has to be impermeable and resistant to the product. Not required when using clinically relevant quantities used in Dental office.			

9. Physical and Chemical Characteristics

Appearance: Light yellow liquid.		Odor: Acetone like with characteristic sweet acrylic ester odor.			
Normal Physical State: Low viscosity liquid		Melting Point: Not Determined Boiling Point: 56.2°C (133°F)		Boiling Point: 56.2°C (133°F)	
Specific Gravity: ~0.9 g/cm ³ Solubility in Water: Partially		pH: 6-8			
Vapor Pressure (mm Hg): 233 mbar @ 20°C		Not Applicable	Evaporation Rate (1	Butyl Acetate=1): Not Applicable	
Other: Not Applicable					

10. Stability and Reactivity Data

Incompatibility (Materials to Avoid): Visible light, high temperatures, strong acids, strong oxidizing agents.		
Hazardous Products Produced During Decomposition: Methacrylates, acrylates, carbon dioxide, carbon monoxide, peroxides and irritating gases.		
Hazardous Polymerization: ☐May Occur ☐May Not Occur ☐Conditions to Avoid: High Temperatures, ignition sources.		
Stability? ⊠Stable ☐Unstable	Conditions to Avoid: High Temperatures, ignition sources.	

11. Toxicological Information

Toxicity Data, Epidemiology Studies, Carcinogenicity, Neurological Effects, Genetic Effects, Reproductive Effects, or Struct		
	turno A otivritre Dotos	
	aire Acrivity Data:	

Product is an irritant to the skin and mucous membranes. The unpolymerized product may be an irritant to the skin in susceptible persons. On the eye the product has an irritating effect. Sensitization: Repeated or prolonged contact with the unpolymerized material may cause sensitization for persons allergic to acrylates and methacrylates. This product shows the following dangers according to internally approved calculation methods for composite materials: Irritant.

ACGIH: A4- Not classifiable as a Human Carcinogen.

Emergency Overview: Material is irritating to eyes, respiratory system and skin. Breathing vapors may cause drowsiness and dizziness.

Emergency ove	i vie w. iviateriai is irritating to eyes, resp	matory bystem and sh	an. Breating rapo	is may cause are wishless and arzemess	
Routes of Exposure	Signs and Symptoms	Single, Repeated, or Lifetime Exposure	Severity (Mild, Moderate,	Acute and Chronic Health Effect(s)	Target Organ(s)
			Severe)		8(-)
Eye	Material can cause irritation.	Single	Moderate	Irritation and possible corneal damage	Yes
Skin	Material may be an irritant and may be absorbed through the skin.	Single & Repeated	Moderate	Irritation or possible allergic response. Severe allergic response may result in breathing difficulties.	Yes
Inhalation	Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. This may not be of concern when using clinically relevant quantities.	Repeated	Moderate	Chronic inhalation may cause effects similar to those of acute inhalation. Causes respiratory tract irritation. May cause motor in coordination and speech abnormalities.	Yes
Ingestion	May cause irritation of the digestive tract. This may not be of concern when using clinically relevant quantities.	Single & Repeated	Mild	Not Applicable	No
Other Central nervous system	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Medical Conditions Aggravated by Exposure Open sores and wounds of the skin. Individuals with known sensitivity to methacrylates, acrylates, or urethane dimethacrylate resin used in Dental restorative products.

Carcinogenicity NTP?: Not listed IARC monographs?: Not listed OSHA regulated?: No. All components of this product are in compliance with the inventory listing Requirements of the U. S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Potential Environmental Effects Do not allow to enter sewers/ surface or ground water.

NFPA Hazard Classification Ratings (Scale 0-4) Health =2, Fire =3, Reactivity=0 Specific Hazard = None

12. Ecological Information

Toxicity Data, Environmental Fate, Physical/Chemical Data, or other Data Supporting Environmental Hazard Statements: Water Hazard class1 (Self-assessment): The acetone in the product will volatilizes, leech and biodegrade when released to the soil. Terrestrial Fate: If release on soil, acetone will both volatilize and leach into the ground. Acetone readily biodegrades and there is evidence suggesting that it biodegrades fairly rapidly in soils. Aquatic Fate: If released into water acetone will probable biodegrade. It is readily biodegradable in screening tests, although data from natural water are lacking. It will also be lost due to volatilization. Adsorption to sediment should not be significant.

13.Disposal Considerations

Regulations: Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Dispose of material as solid waste in a closed container. Dispose of in accordance with Federal, State and Local regulations

Properties (Physical/Chemical) Affecting Disposal: Dispose of material as solid waste in a closed container.

RCRA P-Series: None Listed, RCRA U-Series CAS#67-64-1: Waste Number U002 (Ignitable Waste)

14.Transport Information



Flammable Liquid

Regulated for Shipping: Yes	Proper Shipping Name: Acetone Solution	Packing Group: II
Do Changes in Quantities, packaging, or shipment	Hazard Class: 3	UN Identification Number: 1090
method change product classification? No		

15.Regulatory Information

This product has been classified in accordance with the hazard criteria of the Globally Harmonized System of Classification and Labeling of Chemicals and the SDS contains all of the information required by the Canadian Controlled Products Regulations.

<u>U.S. Federal Regulations</u>: <u>CERCLA 103 Reportable Quantity</u>: RQ is 5,000 pounds (2268Kg) for CAS# 67-64-1 Acetone. Report spills required under federal, state and local regulations. Many states have more stringent release reporting requirements.

RCRA U-Series Hazardous Waste Code for CAS# 67-64-1 Acetone: U002

Section 313 Toxic Chemicals: This product does not contain any chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372).

Section 302 Extremely Hazardous Substances (TPO): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

U.S. State Regulations California Proposition 65: This product does not contain any chemicals, which are on the California Proposition 65 list.

Federal Regulations: The product has been classified and marked in accordance with directives on hazardous materials. Hazard Symbol:

Flammable Water Hazard class1 (Self-assessment): slightly hazardous for water. SARA Codes: CAS # 67-64-1 Acute, chronic, flammable.

International Regulations: Hazard Symbol: Flammable XI F Risk Phrases: R11 Highly Flammable, R36/37/38 Irritating to Eyes, respiratory system and skin. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 Vapors may cause

drowsiness and dizziness. Safety Phrases: S9 Keep container in well-ventilated place. S16 Keep away from sources of ignition – No Smoking, S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice, S28 After contact with skin wash immediately with plenty of water, S61 Avoid release to the environment.

Other: Canada WHMIS for the acetone, classification of B2, D2B. Acetone CAS#67-64-1 is on the Canadian Ingredient Disclosure List.

16.Other Information

To the best of our knowledge this product does not contain gluten, wheat grains, flaxseed, natural rubber, or natural latex.

All components are synthetically produced; none are derived from animal products.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific products features and shall not establish a legally valid contractual relationship.

The attached safety data sheet covers the dangers and measures to be taken when large quantities of material are released, for example due to accidents during transport or storage by the dealer. For quantities of material typically used in clinical practice, information necessary for safe use and storage of the product is given in the DFU.