Revision Date: 09/17/2018 Date of issue: 09/16/2014

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: KREX® Z.O.E. IMPRESSION PASTE **Product Code:** 015100-000, 015101-000, 015102-000

Intended Use of the Product

Designed for use in the preparation of full or partial denture impressions in a custom tray or as a wash. Type II Medium-Bodied.

Name, Address, and Telephone of the Responsible Party

Company

Water Pik, Inc.

1730 East Prospect Road Fort Collins, CO 80553-0001 800/525-2020 (8 am- 4pm MST) Emergency Telephone Number

Emergency Number : 800/424-9300 (24 Hr: CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315 Eye Irrit. 2A H319 Skin Sens. 1 H317 STOT RE 2 H373 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)







Version: 1.0

Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US): P260 - Do not breathe vapors, mist, spray.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling. P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective clothing, protective gloves, eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see Section 4).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

EN (English US)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Name | Product Identifier | % (w/w) | Classification (GHS-US) |
|--------------------------------------|---------------------|--|---------------------------|
| Zinc oxide | (CAS No) 1314-13-2 | 0.1 to 1, 1 to 5, 5 to 10, 10 to 30, | Aquatic Acute 1, H400 |
| | | 30 to 60, or 60 to 87 | Aquatic Chronic 1, H410 |
| Rosin, polymerized | (CAS No) 65997-05-9 | 0.1 to 1, 1 to 5, 5 to 10, 10 to 30, | Not classified |
| | | or 30 to 32 | |
| Talc | (CAS No) 14807-96-6 | 0.1 to 1, 1 to 5, 5 to 10, or 10 to 17 | Comb. Dust |
| | | | STOT RE 2, H373 |
| Cottonseed oil | (CAS No) 8001-29-4 | 0.1 to 1, 1 to 5, 5 to 10, or 10 to 13 | Not classified |
| Eugenol | (CAS No) 97-53-0 | 0.1 to 1, 1 to 5, or 5 to 10 | Acute Tox. 4 (Oral), H302 |
| | | | Eye Irrit. 2A, H319 |
| | | | Skin Sens. 1, H317 |
| Fatty acids, linseed-oil | (CAS No) 68424-45-3 | 0.1 to 1, 1 to 5, or 5 to 7 | Not classified |
| Petrolatum | (CAS No) 8009-03-8 | 0.1 to 1, 1 to 5, or 5 to 7 | Not classified |
| Paraffin waxes and Hydrocarbon waxes | (CAS No) 8002-74-2 | 0.1 to 1 or 1 to 4 | Comb. Dust |
| Olive oil | (CAS No) 8001-25-0 | 0.1 to 1 or 1 to 3 | Not classified |
| Acetic acid | (CAS No) 64-19-7 | 0.1 to 1 | Flam. Liq. 3, H226 |
| | | | Skin Corr. 1A, H314 |
| | | | Eye Dam. 1, H318 |
| | | | Aquatic Acute 3, H402 |

More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER or doctor/physician if you feel unwell. Keep at rest and in a position comfortable for breathing.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation persists. Wash with plenty of soap and water.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Obtain medical attention if irritation persists.

Ingestion: Rinse mouth. Do NOT induce vomiting.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.

Inhalation: May cause respiratory irritation. Inhalation of fumes may cause metal fume fever.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged inhalation may damage lungs.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

EN (English US) 2/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Hazardous Combustion Products: Irritating fumes. Oxides of zinc and carbon. Hydrocarbons. If heated to the point of fume generation zinc fumes may cause metal fume fever.

Reference to Other Sections Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Do not allow product to spread into the environment.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: As an immediate precautionary measure, isolate spill or leak area in all directions. Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Contact competent authorities after a spill.

Reference to Other Sections See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

<u>Specific End Use(s)</u> Designed for use in the preparation of full or partial denture impressions in a custom tray or as a wash. Type II Medium-Bodied.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

| Zinc oxide (1314-13-2) | | |
|------------------------|------------------------|----------------------|
| USA ACGIH | ACGIH TWA (mg/m³) | 2 mg/m³ |
| USA ACGIH | ACGIH STEL (mg/m³) | 10 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ |

EN (English US) 3/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| | 7, No. 58 / Monday, March 26, 2012 / Rules Ar | |
|-------------------------|---|--|
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (STEL) (mg/m³) | 10 mg/m ³ |
| USA NIOSH | NIOSH REL (ceiling) (mg/m³) | 15 mg/m³ |
| USA IDLH | US IDLH (mg/m³) | 500 mg/m ³ |
| Alberta | OEL STEL (mg/m³) | 10 mg/m ³ |
| Alberta | OEL TWA (mg/m³) | 2 mg/m³ |
| British Columbia | OEL STEL (mg/m³) | 10 mg/m³ |
| British Columbia | OEL TWA (mg/m³) | 2 mg/m³ |
| Manitoba | OEL STEL (mg/m³) | 10 mg/m³ |
| Manitoba | OEL TWA (mg/m³) | 2 mg/m³ |
| New Brunswick | OEL STEL (mg/m³) | 10 mg/m ³ |
| New Brunswick | OEL TWA (mg/m³) | 5 mg/m³ |
| Newfoundland & Labrador | OEL STEL (mg/m³) | 10 mg/m³ |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 2 mg/m³ |
| Nova Scotia | OEL STEL (mg/m³) | 10 mg/m ³ |
| Nova Scotia | OEL TWA (mg/m³) | 2 mg/m³ |
| Nunavut | OEL STEL (mg/m³) | 10 mg/m³ |
| Nunavut | OEL TWA (mg/m³) | 10 mg/m³ (total mass) |
| Northwest Territories | OEL STEL (mg/m³) | 10 mg/m ³ |
| Northwest Territories | OEL TWA (mg/m³) | 10 mg/m³ (total mass) |
| Ontario | OEL STEL (mg/m³) | 10 mg/m ³ |
| Ontario | OEL TWA (mg/m³) | 2 mg/m³ |
| Prince Edward Island | OEL STEL (mg/m³) | 10 mg/m³ |
| Prince Edward Island | OEL TWA (mg/m³) | 2 mg/m³ |
| Québec | VECD (mg/m³) | 10 mg/m³ |
| Québec | VEMP (mg/m³) | 5 mg/m³ |
| Saskatchewan | OEL STEL (mg/m³) | 10 mg/m³ |
| Saskatchewan | OEL TWA (mg/m³) | 2 mg/m³ |
| Yukon | OEL STEL (mg/m³) | 20 mg/m ³ |
| Yukon | OEL TWA (mg/m³) | 10 mg/m ³ |
| Talc (14807-96-6) | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 2 mg/m³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 2 mg/m³ (containing no Asbestos and <1% Quartz) |
| USA IDLH | US IDLH (mg/m³) | 1000 mg/m³ (containing no asbestos and <1% quartz) |
| Alberta | OEL TWA (mg/m³) | 2 mg/m³ |
| British Columbia | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Manitoba | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| New Brunswick | OEL TWA (mg/m³) | 2 mg/m³ |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Nova Scotia | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Nunavut | OEL TWA (mg/m³) | 6 mg/m³ (total mass) |
| Northwest Territories | OEL TWA (mg/m³) | 6 mg/m³ (total mass) |
| Ontario | OEL TWA (mg/m³) | 2 mg/m³ (containing no Asbestos and <1% Crystalline |
| | , , | silica) |
| Prince Edward Island | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica) |
| Québec | VEMP (mg/m³) | 3 mg/m³ |
| | 1 0, , | , 0, |

EN (English US) 4/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| Saskatchewan | OEL TWA (mg/m³) | 2 mg/m³ |
|--|--------------------------|-----------|
| Yukon | OEL TWA (mg/m³) | 20 mppcf |
| Paraffin waxes and Hydrocarbon waxes (8002-74-2) | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 2 mg/m³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 2 mg/m³ |
| Alberta | OEL TWA (mg/m³) | 2 mg/m³ |
| British Columbia | OEL TWA (mg/m³) | 2 mg/m³ |
| Manitoba | OEL TWA (mg/m³) | 2 mg/m³ |
| New Brunswick | OEL TWA (mg/m³) | 2 mg/m³ |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 2 mg/m³ |
| Nova Scotia | OEL TWA (mg/m³) | 2 mg/m³ |
| Nunavut | OEL STEL (mg/m³) | 6 mg/m³ |
| Nunavut | OEL TWA (mg/m³) | 2 mg/m³ |
| Northwest Territories | OEL STEL (mg/m³) | 6 mg/m³ |
| Northwest Territories | OEL TWA (mg/m³) | 2 mg/m³ |
| Ontario | OEL TWA (mg/m³) | 2 mg/m³ |
| Prince Edward Island | OEL TWA (mg/m³) | 2 mg/m³ |
| Québec | VEMP (mg/m³) | 2 mg/m³ |
| Saskatchewan | OEL STEL (mg/m³) | 4 mg/m³ |
| Saskatchewan | OEL TWA (mg/m³) | 2 mg/m³ |
| Yukon | OEL STEL (mg/m³) | 6 mg/m³ |
| Yukon | OEL TWA (mg/m³) | 2 mg/m³ |
| Acetic acid (64-19-7) | | |
| USA ACGIH | ACGIH TWA (ppm) | 10 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 15 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 25 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 10 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 25 mg/m³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 10 ppm |
| USA NIOSH | NIOSH REL (STEL) (mg/m³) | 37 mg/m³ |
| USA NIOSH | NIOSH REL (STEL) (ppm) | 15 ppm |
| USA IDLH | US IDLH (ppm) | 50 ppm |
| Alberta | OEL STEL (mg/m³) | 37 mg/m³ |
| Alberta | OEL STEL (ppm) | 15 ppm |
| Alberta | OEL TWA (mg/m³) | 25 mg/m³ |
| Alberta | OEL TWA (ppm) | 10 ppm |
| British Columbia | OEL STEL (ppm) | 15 ppm |
| British Columbia | OEL TWA (ppm) | 10 ppm |
| Manitoba | OEL STEL (ppm) | 15 ppm |
| Manitoba | OEL TWA (ppm) | 10 ppm |
| New Brunswick | OEL STEL (mg/m³) | 37 mg/m³ |
| New Brunswick | OEL STEL (ppm) | 15 ppm |
| New Brunswick | OEL TWA (mg/m³) | 25 mg/m³ |
| New Brunswick | OEL TWA (ppm) | 10 ppm |
| Newfoundland & Labrador | OEL STEL (ppm) | 15 ppm |
| Newfoundland & Labrador | OEL TWA (ppm) | 10 ppm |
| Nova Scotia | OEL STEL (ppm) | 15 ppm |
| Nova Scotia | OEL TWA (ppm) | 10 ppm |
| Nunavut | OEL STEL (mg/m³) | 39 mg/m³ |
| Nunavut | OEL STEL (ppm) | 15 ppm |
| Nunavut | OEL TWA (mg/m³) | 26 mg/m³ |
| | · · · · · · · · · · / | ···o/ ··· |

EN (English US) 5/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| <u> </u> | ·, · · · · · · · · · · · · · · · · · · | |
|-----------------------|--|----------|
| Nunavut | OEL TWA (ppm) | 10 ppm |
| Northwest Territories | OEL STEL (mg/m³) | 39 mg/m³ |
| Northwest Territories | OEL STEL (ppm) | 15 ppm |
| Northwest Territories | OEL TWA (mg/m³) | 26 mg/m³ |
| Northwest Territories | OEL TWA (ppm) | 10 ppm |
| Ontario | OEL STEL (ppm) | 15 ppm |
| Ontario | OEL TWA (ppm) | 10 ppm |
| Prince Edward Island | OEL STEL (ppm) | 15 ppm |
| Prince Edward Island | OEL TWA (ppm) | 10 ppm |
| Québec | VECD (mg/m³) | 37 mg/m³ |
| Québec | VECD (ppm) | 15 ppm |
| Québec | VEMP (mg/m³) | 25 mg/m³ |
| Québec | VEMP (ppm) | 10 ppm |
| Saskatchewan | OEL STEL (ppm) | 15 ppm |
| Saskatchewan | OEL TWA (ppm) | 10 ppm |
| Yukon | OEL STEL (mg/m³) | 43 mg/m³ |
| Yukon | OEL STEL (ppm) | 25 ppm |
| Yukon | OEL TWA (mg/m³) | 25 mg/m³ |
| Yukon | OEL TWA (ppm) | 10 ppm |
| | | |

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.







Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wash contaminated clothing before reuse.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed

Not available

established Occupational Exposure Limits.

Relative Vapor Density at 20 °C

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<u>Information on Basic Physical and Chemical Properties</u>

Physical State : Liquid

Appearance : Tan. Base: Red, Hardener: White

Odor Clove-like **Odor Threshold** Not available Not available Not available **Evaporation Rate** Freezing/Melting Point Not available **Boiling Point** Not available **Flash Point** Not available **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Upper/Lower Flammable Limit** Not available Not available **Vapor Pressure**

EN (English US) 6/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Specific Gravity : 1-3

Solubility : Not soluble in water

Partition Coefficient: N-octanol/water : Not available Viscosity : Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact. Explosion Data – Sensitivity to Static Discharge : Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

<u>Chemical Stability</u>: The product is stable at normal handling and storage conditions. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

Conditions to Avoid: Extremely high or low temperatures. Sources of ignition. Incompatible materials.

<u>Incompatible Materials</u>: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: None known.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Inhalation of fumes may cause metal fume fever.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged inhalation may damage lungs.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| 2250 and 2050 2 ata. | |
|--|--------------------------|
| Zinc oxide (1314-13-2) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 2000 mg/kg |
| Eugenol (97-53-0) | |
| LD50 Oral Rat | 1930 mg/kg |
| Petrolatum (8009-03-8) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 2000 mg/kg read across |
| LD50 Dermal Rabbit | 3600 mg/kg |
| Paraffin waxes and Hydrocarbon waxes (8002-74-2) | |
| LD50 Oral Rat | > 3750 mg/kg |
| LD50 Dermal Rabbit | > 3600 mg/kg |
| Acetic acid (64-19-7) | |
| LD50 Oral Rat | 3310 mg/kg |
| LD50 Dermal Rabbit | 1060 μl/kg |
| LC50 Inhalation Rat | 11.4 mg/l/4h |

EN (English US) 7/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| Talc (14807-96-6) | |
|--|--|
| IARC Group | 3 |
| National Toxicity Program (NTP) Status | Evidence of Carcinogenicity, Twelfth Report - Items under consideration. |
| Eugenol (97-53-0) | |
| IARC Group | 3 |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

| Zinc oxide (1314-13-2) | te inc. Very toxic to adduct the with long lasting circus. | |
|------------------------|--|--|
| LC50 Fish 1 | 780 μg/l (Exposure time: 96 h - Species: Pimephales promelas) | |
| EC50 Daphnia 1 | 0.122 mg/l | |
| NOEC chronic fish | 0.026 mg/l (Species: Jordanella floridae) | |
| Talc (14807-96-6) | | |
| LC50 Fish 1 | > 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static]) | |
| Petrolatum (8009-03-8) | | |
| LC50 Fish 1 | > 1000 mg/l LLO; insoluble in water | |
| NOEC (chronic) | > 1000 mg/l | |
| NOEC chronic fish | > 1000 mg/l | |
| Acetic acid (64-19-7) | | |
| LC50 Fish 1 | 79 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) | |
| EC50 Daphnia 1 | 65 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) | |
| LC 50 Fish 2 | 75 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) | |

Persistence and Degradability

Not established. May cause long-term adverse effects in the environment.

Bioaccumulative Potential

| KREX® Z.O.E. IMPRESSION PASTE | | |
|-------------------------------|----------------------------|--|
| Bioaccumulative Potential | | |
| Talc (14807-96-6) | | |
| BCF Fish 1 | (no known bioaccumulation) | |
| Petrolatum (8009-03-8) | | |
| Log Pow | > 6 Calculated | |
| Acetic acid (64-19-7) | | |
| Log Pow | -0.31 (at 20 °C) | |

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Not regulated for transport

In Accordance with IMDG

Not regulated for transport

In Accordance with IATA

Not regulated for transport

EN (English US) 8/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

| KDEA® | 7 O E | INADDECC | ION PASTE | : |
|-------|---------|----------|-----------|---|
| KKFX" | /.().F. | HVIPKESS | IUN PASIF | • |

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard

Zinc oxide (1314-13-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Rosin, polymerized (65997-05-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Talc (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cottonseed oil (8001-29-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

Eugenol (97-53-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Fatty acids, linseed-oil (68424-45-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA
Regulatory Flag

Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

Petrolatum (8009-03-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Olive oil (8001-25-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Acetic acid (64-19-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Zinc oxide (1314-13-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Talc (14807-96-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Cottonseed oil (8001-29-4)

U.S. - Pennsylvania - RTK (Right to Know) List

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Acetic acid (64-19-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

EN (English US) 9/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Canadian Regulations

KREX® Z.O.E. IMPRESSION PASTE

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects





Zinc oxide (1314-13-2)

Listed on the Canadian DSL (Domestic Sustances List), Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Rosin, polymerized (65997-05-9)

Listed on the Canadian DSL (Domestic Sustances List)

Talc (14807-96-6)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Cottonseed oil (8001-29-4)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Eugenol (97-53-0)

Listed on the Canadian DSL (Domestic Sustances List)

Fatty acids, linseed-oil (68424-45-3)

Listed on the Canadian DSL (Domestic Sustances List)

Petrolatum (8009-03-8)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Olive oil (8001-25-0)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Acetic acid (64-19-7)

Listed on the Canadian DSL (Domestic Sustances List), Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Class B Division 3 - Combustible Liquid

Class E - Corrosive Material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 09/17/2018

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
|---------------------|--|
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Acute 3 | Hazardous to the aquatic environment - Acute Hazard Category 3 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |

EN (English US) 10/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| Comb. Dust | Combustible Dust |
|---------------|---|
| | |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Skin Corr. 1A | Skin corrosion/irritation Category 1A |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| Skin Sens. 1 | Skin sensitization Category 1 |
| STOT RE 2 | Specific target organ toxicity (repeated exposure) Category 2 |
| H226 | Flammable liquid and vapor |
| Comb. Dust | May form combustible dust concentrations in air |
| H302 | Harmful if swallowed |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |

Party Responsible for the Preparation of This Document

Water Pik, Inc.

Telephone: 800-525-2020

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

EN (English US) 11/11