



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 39-0593-2
Issue Date: 06/05/19

Version Number: 1.01
Supersedes Date: 06/26/18

Product identifier

3M™ IMPREGUM™ PENTA™ SUPER QUICK Heavy Body/Light Body Kit

ID Number(s):

UU-0093-0691-9, UU-0098-0622-3

7100157683, 7100196388

Recommended use

Dental Product, Impression Material

Restrictions on use

For use only by dental professionals in approved indications.

Supplier's details

MANUFACTURER: 3M
DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

37-8996-3, 37-8947-6, 37-9001-1, 37-9021-9

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may

have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 37-9001-1
Issue Date: 08/26/19

Version Number: 2.00
Supersedes Date: 06/13/17

SECTION 1: Identification

1.1. Product identifier

3M™ Impregum Super Quick LB Catalyst

Product Identification Numbers

LE-F100-2233-3

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Materials

Restrictions on use

For use only by dental professionals in approved indications.

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Oral Care Solutions Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Skin Sensitizer: Category 1B.

Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure:
blood or blood-forming organs |

sensory organs |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only in a well-ventilated area.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
CITRIC ESTER	77-90-7	35 - 45 Trade Secret *
SILANE TREATED SILICA	68909-20-6	20 - 30 Trade Secret *
SULFONIUM SALT	72140-65-9	< 25 Trade Secret *
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	68855-54-9	1 - 20 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes. Use personal protective equipment (gloves, respirators, etc.) as required. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Cristobalite	68855-54-9	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Cristobalite	68855-54-9	OSHA	TWA concentration(respirable):0.05 mg/m3(1.2 millions of particles/cu. ft.);TWA:0.05 mg/m3	
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	
SILICA, AMORPHOUS	68909-20-6	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Physical state

Solid

Color

White

Specific Physical Form:

Paste

Odor

Characteristic Odor

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

Not Applicable

Flash Point

No flash point

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Classified

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)

Not Applicable

Vapor Pressure

Not Applicable

Vapor Density

Not Applicable

Density

1.2 - 1.4 g/cm³

Specific Gravity

1.2 - 1.4 [Ref Std: WATER=1]

Solubility in Water

Negligible

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

Not Applicable

Decomposition temperature

No Data Available

Viscosity

No Data Available

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Bone Marrow Effects: Signs/symptoms may include generalized weakness, pallor of the skin, fatty infiltration of the bone marrow, decreases in the numbers of circulating blood cells, increased susceptibility to infection.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTAL AIRRESP	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTAL AIRRESP	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
Generic: Cristobalite	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
CITRIC ESTER	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
CITRIC ESTER	Ingestion	Rat	LD50 > 25,000 mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
SULFONIUM SALT	Dermal	Rat	LD50 > 2,000 mg/kg
SULFONIUM SALT	Ingestion	Rat	LD50 300-2,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In vitro data	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
SILANE TREATED SILICA	Human and animal	Not classified

SULFONIUM SALT	Mouse	Sensitizing
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Mouse	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SILANE TREATED SILICA	In Vitro	Not mutagenic
SULFONIUM SALT	In Vitro	Not mutagenic
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED SILICA	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	Human and animal	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
SULFONIUM SALT	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	premating into lactation
SULFONIUM SALT	Ingestion	Toxic to female reproduction	Rat	NOAEL 30 mg/kg/day	premating into lactation
SULFONIUM SALT	Ingestion	Toxic to male reproduction	Rat	NOAEL 30 mg/kg/day	30 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SULFONIUM SALT	Ingestion	respiratory system	Not classified	Rat	NOAEL 300 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
SULFONIUM SALT	Ingestion	bone marrow	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 10 mg/kg/day	30 days
SULFONIUM SALT	Ingestion	respiratory system	May cause damage to organs through prolonged or repeated exposure	Rat	NOAEL 30 mg/kg/day	30 days
SULFONIUM SALT	Ingestion	eyes	May cause damage to organs through prolonged or repeated exposure	Rat	NOAEL 100 mg/kg/day	30 days
SULFONIUM SALT	Ingestion	hematopoietic	Not classified	Rat	NOAEL 300	30 days

		system liver immune system kidney and/or bladder			mg/kg/day	
SULFONIUM SALT	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 30 mg/kg/day	30 days
SULFONIUM SALT	Ingestion	auditory system heart skin endocrine system bone, teeth, nails, and/or hair muscles nervous system vascular system	Not classified	Rat	NOAEL 300 mg/kg/day	30 days
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 3,738 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 37-9001-1
Issue Date: 08/26/19

Version Number: 2.00
Supersedes Date: 06/13/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	37-8996-3	Version Number:	1.01
Issue Date:	04/06/18	Supersedes Date:	06/13/17

SECTION 1: Identification

1.1. Product identifier

3M™ Impregum™ Penta™ Super Quick HB Base

Product Identification Numbers

LE-F100-2233-1

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use only by dental professionals in approved indications.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms**Hazard Statements**

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Furan, tetrahydro-, polymer with oxirane, bis[[3-(1-aziridinyl)butyl]carbamate]	110531-92-5	40 - 60 Trade Secret *
FATTY ACID TRIGLYCERIDES	67701-27-3	10 - 30 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	1 - 20 Trade Secret *
DIBENZYL TOLUENE	26898-17-9	1 - 20 Trade Secret *
N-ETHYL-P-TOLUENESULFONAMIDE	80-39-7	1 - 10 Trade Secret *
ZINC OXIDE	1314-13-2	< 2 Trade Secret *
1-DODECYLIMIDAZOLE	4303-67-7	< 1 Trade Secret *
Oils, mint, Mentha arvensis piperascensis, var. piperascens, Labiatae.	68917-18-0	< 0.5 Trade Secret *
TITANIUM DIOXIDE	13463-67-7	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ZINC OXIDE	1314-13-2	OSHA	TWA(as fume):5 mg/m3;TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
ZINC OXIDE	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m3;STEL(respirable fraction):10 mg/m3	
TITANIUM DIOXIDE	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
TITANIUM DIOXIDE	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Cristobalite	68855-54-9	OSHA	TWA concentration(respirable):0.05 mg/m3(1.2 millions of particles/cu. ft.);TWA:0.05 mg/m3	
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	
Cristobalite	68855-54-9	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	mint odor, blue paste
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Density	1 - 1.2 g/cm3
Specific Gravity	> 1 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	<i>No Data Available</i>

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Carcinogenicity:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
SILICA, CRYSTALLINE	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

SILICA, CRYSTAL AIRRESP	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
Generic: Cristobalite	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
TITANIUM DIOXIDE	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Furan, tetrahydro-, polymer with oxirane, bis[[3-(1-aziridinyl)butyl]carbamate]	Dermal	Professional judgement	LD50 Not applicable
Furan, tetrahydro-, polymer with oxirane, bis[[3-(1-aziridinyl)butyl]carbamate]	Ingestion	Rat	LD50 > 2,000 mg/kg
FATTY ACID TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg
FATTY ACID TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg
DIATOMACEOUS EARTH	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Ingestion	Rat	LD50 > 10,360 mg/kg
N-ETHYL-P-TOLUENESULFONAMIDE	Dermal	Rabbit	LD50 > 5,000 mg/kg
N-ETHYL-P-TOLUENESULFONAMIDE	Ingestion	similar compounds	LD50 estimated to be 300 - 2,000 mg/kg
ZINC OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC OXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
ZINC OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
1-DODECYLIMIDAZOLE	Ingestion	Rat	LD50 641 mg/kg
Oils, mint, Mentha arvensis piperascensis, var. piperascens, Labiatae.	Dermal	Rabbit	LD50 > 5,000 mg/kg
Oils, mint, Mentha arvensis piperascensis, var. piperascens, Labiatae.	Ingestion	Rat	LD50 1,240 mg/kg
TITANIUM DIOXIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TITANIUM DIOXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
TITANIUM DIOXIDE	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Furan, tetrahydro-, polymer with oxirane, bis[[3-(1-aziridinyl)butyl]carbamate]	Rabbit	No significant irritation
DIATOMACEOUS EARTH	In vitro data	No significant irritation
ZINC OXIDE	Human and animal	No significant irritation
1-DODECYLIMIDAZOLE	Rabbit	Mild irritant
Oils, mint, Mentha arvensis piperascensis, var. piperascens, Labiatae.	Rabbit	Mild irritant
TITANIUM DIOXIDE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Furan, tetrahydro-, polymer with oxirane, bis[[3-(1-aziridinyl)butyl]carbamate]	Rabbit	Moderate irritant
DIATOMACEOUS EARTH	Rabbit	Mild irritant
ZINC OXIDE	Rabbit	Mild irritant
1-DODECYLIMIDAZOLE	In vitro data	Severe irritant
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	In vitro data	Severe irritant
TITANIUM DIOXIDE	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Furan, tetrahydro-, polymer with oxirane, bis[[3-(1-aziridinyl)butyl]carbamate]	Guinea pig	Not classified
DIATOMACEOUS EARTH	Mouse	Not classified
ZINC OXIDE	Guinea pig	Not classified
1-DODECYLIMIDAZOLE	Mouse	Sensitizing
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	Guinea pig	Sensitizing
TITANIUM DIOXIDE	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Furan, tetrahydro-, polymer with oxirane, bis[[3-(1-aziridinyl)butyl]carbamate]	In Vitro	Not mutagenic
DIATOMACEOUS EARTH	In Vitro	Some positive data exist, but the data are not sufficient for classification
ZINC OXIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification
ZINC OXIDE	In vivo	Some positive data exist, but the data are not sufficient for classification
1-DODECYLIMIDAZOLE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
DIATOMACEOUS EARTH	Inhalation	Human and animal	Carcinogenic
TITANIUM DIOXIDE	Ingestion	Multiple animal species	Not carcinogenic
TITANIUM DIOXIDE	Inhalation	Rat	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
ZINC OXIDE	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	prematuring & during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DIATOMACEOUS EARTH	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
DIATOMACEOUS EARTH	Ingestion	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 3,738 mg/kg/day	90 days
ZINC OXIDE	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
ZINC OXIDE	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
TITANIUM DIOXIDE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
TITANIUM DIOXIDE	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
ZINC OXIDE (ZINC COMPOUNDS)	1314-13-2	< 2

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
HEXANE	110-54-3	Male reproductive toxin

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 37-8996-3 Version Number: 1.01

Issue Date: 04/06/18

Supersedes Date: 06/13/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	37-8947-6	Version Number:	1.01
Issue Date:	03/07/18	Supersedes Date:	06/19/17

SECTION 1: Identification

1.1. Product identifier

3M™ Impregum™ Super Quick Light Body Base

Product Identification Numbers

LE-F100-2231-8

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use only by dental professionals in approved indications.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms**Hazard Statements**

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	68917-18-0	< 1 Trade Secret *
POLYETHER	110531-92-5	50 - 70 Trade Secret *
CRISTOBALITE	14464-46-1	1 - 20 Trade Secret *
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 20 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 10 Trade Secret *
N-ETHYL-P-TOLUENESULFONAMIDE	80-39-7	1 - 10 Trade Secret *
Zinc Oxide	1314-13-2	1 - 10 Trade Secret *
Zeolites	1318-02-1	1 - 10 Trade Secret *
Zinc Stearate	557-05-1	1 - 5 Trade Secret *
1-DODECYLIMIDAZOLE	4303-67-7	< 1 Trade Secret *
C.I. PIGMENT BLUE 28	1345-16-0	< 0.5 Trade Secret *
Titanium Dioxide	13463-67-7	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate

authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m3;STEL(respirable fraction):10 mg/m3	
Zinc Oxide	1314-13-2	OSHA	TWA(as fume):5 mg/m3;TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Aluminum, insoluble compounds	1318-02-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Cobalt, inorganic compounds	1345-16-0	ACGIH	TWA(as Co):0.02 mg/m3	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
CRISTOBALITE	14464-46-1	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
CRISTOBALITE	14464-46-1	OSHA	TWA concentration(respirable):0.05 mg/m3(1.2 millions of particles/cu. ft.);TWA:0.05 mg/m3	
STEARATES	557-05-1	ACGIH	TWA(inhalable fraction):10 mg/m3;TWA(respirable fraction):3 mg/m3	A4: Not class. as human carcin
Zinc Stearate	557-05-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	mint odor, green paste
Odor threshold	No Data Available
pH	Not Applicable
Melting point	Not Applicable
Boiling Point	Not Applicable
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapor Pressure	No Data Available
Vapor Density	No Data Available
Density	1 - 1.2 g/cm ³
Specific Gravity	> 1 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Molecular weight	No Data Available
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H ₂ O & Exempt Solvents	No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Carcinogenicity:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTALLINE	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens
Generic: Cobalt compounds	1345-16-0	Anticipated human carcinogen	National Toxicology Program Carcinogens
Generic: Cobalt and inorganic cobalt compounds	1345-16-0	Grp. 2B: Possible human carcinogen	International Agency for Research on Cancer
Generic: Cobalt and inorganic cobalt compounds	1345-16-0	Anticipated human carcinogen	National Toxicology Program Carcinogens
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carcinogen	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
POLYETHER	Dermal	Professional judgment	LD50 Not applicable
POLYETHER	Ingestion	Rat	LD50 > 2,000 mg/kg
CRISTOBALITE	Dermal		LD50 estimated to be > 5,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50 5,700 mg/kg
FATTY ACIDS TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg
FATTY ACIDS TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg
N-ETHYL-P-TOLUENESULFONAMIDE	Dermal	Rabbit	LD50 > 5,000 mg/kg
N-ETHYL-P-TOLUENESULFONAMIDE	Ingestion	similar compounds	LD50 estimated to be 300 - 2,000 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Zeolites	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zeolites	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.57 mg/l
Zeolites	Ingestion	Rat	LD50 > 5,000 mg/kg
Zinc Stearate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zinc Stearate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Zinc Stearate	Ingestion	Rat	LD50 > 5,000 mg/kg
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	Dermal	Rabbit	LD50 > 5,000 mg/kg
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	Ingestion	Rat	LD50 1,240 mg/kg

1-DODECYLIMIDAZOLE	Ingestion	Rat	LD50 641 mg/kg
C.I. PIGMENT BLUE 28	Dermal		LD50 estimated to be > 5,000 mg/kg
C.I. PIGMENT BLUE 28	Ingestion	Rat	LD50 > 10,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
POLYETHER	Rabbit	No significant irritation
CRISTOBALITE	Professional judgement	No significant irritation
Zinc Oxide	Human and animal	No significant irritation
Zeolites	Rabbit	No significant irritation
Zinc Stearate	Rabbit	No significant irritation
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	Rabbit	Mild irritant
1-DODECYLIMIDAZOLE	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
POLYETHER	Rabbit	Moderate irritant
Zinc Oxide	Rabbit	Mild irritant
Zeolites	Rabbit	Mild irritant
Zinc Stearate	Rabbit	No significant irritation
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	In vitro data	Severe irritant
1-DODECYLIMIDAZOLE	In vitro data	Severe irritant
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
POLYETHER	Guinea pig	Not classified
Zinc Oxide	Guinea pig	Not classified
Oils, mint, Mentha arvensis piperascenssis, var. piperascens, Labiatae.	Guinea pig	Sensitizing
1-DODECYLIMIDAZOLE	Mouse	Sensitizing
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
POLYETHER	In Vitro	Not mutagenic
CRISTOBALITE	In Vitro	Some positive data exist, but the data are not sufficient for classification

CRISTOBALITE	In vivo	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
1-DODECYLIMIDAZOLE	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
CRISTOBALITE	Inhalation	Human and animal	Carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Zinc Oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CRISTOBALITE	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Zinc Oxide (ZINC COMPOUNDS)	1314-13-2	1 - 10
Zinc Stearate (ZINC COMPOUNDS)	557-05-1	1 - 5
C.I. PIGMENT BLUE 28 (Cobalt, inorganic compounds)	1345-16-0	< 0.5

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
HEXANE	110-54-3	Male reproductive toxin
Toluene	108-88-3	Developmental Toxin

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 37-8947-6
Issue Date: 03/07/18

Version Number: 1.01
Supersedes Date: 06/19/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	37-9021-9	Version Number:	2.00
Issue Date:	09/17/18	Supersedes Date:	06/20/17

SECTION 1: Identification

1.1. Product identifier

3M™ Impregum™ Penta™ Super Quick HB Catalyst

Product Identification Numbers

LE-F100-2234-6

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use only by dental professionals in approved indications.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms**Hazard Statements**

Causes skin irritation.

May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

10% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Sulfonium, [2-carboxy-1-(carboxymethyl)ethyl]dodecylethyl-, mixed Me and pentyl diesters, tetrafluoroborates	2220260-54-6	20 - 40 Trade Secret *
2,6-DI-TERT-BUTYL-P-CRESOL	128-37-0	< 0.5 Trade Secret *
C.I. PIGMENT RED 112	6535-46-2	< 0.5 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	10 - 30 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	10 - 30 Trade Secret *
SILANE TREATED SILICA containing respirable fraction 1-<10%	68909-20-6	10 - 30 Trade Secret *
PLASTICIZER	82469-79-2	1 - 30 Trade Secret *
POLY(TETRAMETHYLENE ETHER)	25190-06-1	< 5 Trade Secret *
TITANIUM DIOXIDE	13463-67-7	< 2 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
2,6-DI-TERT-BUTYL-P-CRESOL	128-37-0	ACGIH	TWA(inhalable fraction and vapor):2 mg/m3	A4: Not class. as human carcin
TITANIUM DIOXIDE	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
TITANIUM DIOXIDE	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Cristobalite	68855-54-9	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Cristobalite	68855-54-9	OSHA	TWA concentration(respirable):0.05 mg/m3(1.2 millions of particles/cu. ft.);TWA:0.05 mg/m3	
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	
SILICA, AMORPHOUS	68909-20-6	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	Dark red color, slightly acrid odor
Odor threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point	<i>No Data Available</i>
Boiling Point	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Specific Gravity	1.1 - 1.4 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Percent volatile	<i>Not Applicable</i>
VOC Less H2O & Exempt Solvents	<i>Not Applicable</i>

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Carcinogenicity:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:
Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
SILICA, CRYSTALLINE	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTALLINE	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
TITANIUM DIOXIDE	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Sulfonium, [2-carboxy-1-(carboxymethyl)ethyl]dodecylethyl-, mixed Me and pentyl diesters, tetrafluoroborates	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Sulfonium, [2-carboxy-1-(carboxymethyl)ethyl]dodecylethyl-, mixed Me and pentyl diesters, tetrafluoroborates	Ingestion	Rat	LD50 > 2,000 mg/kg
SILANE TREATED SILICA containing respirable fraction 1-<10%	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA containing respirable fraction 1-<10%	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SILANE TREATED SILICA containing respirable fraction 1-<10%	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50 5,700 mg/kg
DIATOMACEOUS EARTH	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 2,000 mg/kg
TITANIUM DIOXIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TITANIUM DIOXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
TITANIUM DIOXIDE	Ingestion	Rat	LD50 > 10,000 mg/kg
2,6-DI-TERT-BUTYL-P-CRESOL	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	Rat	LD50 > 2,930 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Sulfonium, [2-carboxy-1-(carboxymethyl)ethyl]dodecylethyl-, mixed Me and pentyl diesters, tetrafluoroborates	Professional judgement	Irritant
SILANE TREATED SILICA containing respirable fraction 1-<10%	Rabbit	No significant irritation
DIATOMACEOUS EARTH	In vitro data	No significant irritation
TITANIUM DIOXIDE	Rabbit	No significant irritation
2,6-DI-TERT-BUTYL-P-CRESOL	Human and animal	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Sulfonium, [2-carboxy-1-(carboxymethyl)ethyl]dodecylethyl-, mixed Me and pentyl diesters, tetrafluoroborates	In vitro data	No significant irritation
SILANE TREATED SILICA containing respirable fraction 1-<10%	Rabbit	No significant irritation
DIATOMACEOUS EARTH	Rabbit	Mild irritant
TITANIUM DIOXIDE	Rabbit	No significant irritation

2,6-DI-TERT-BUTYL-P-CRESOL	Rabbit	Mild irritant
----------------------------	--------	---------------

Skin Sensitization

Name	Species	Value
Sulfonium, [2-carboxy-1-(carboxymethyl)ethyl]dodecylethyl-, mixed Me and pentyl diesters, tetrafluoroborates	In vitro data	Sensitizing
SILANE TREATED SILICA containing respirable fraction 1-<10%	Human and animal	Not classified
DIATOMACEOUS EARTH	Mouse	Not classified
TITANIUM DIOXIDE	Human and animal	Not classified
2,6-DI-TERT-BUTYL-P-CRESOL	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Sulfonium, [2-carboxy-1-(carboxymethyl)ethyl]dodecylethyl-, mixed Me and pentyl diesters, tetrafluoroborates	In Vitro	Not mutagenic
SILANE TREATED SILICA containing respirable fraction 1-<10%	In Vitro	Not mutagenic
DIATOMACEOUS EARTH	In Vitro	Some positive data exist, but the data are not sufficient for classification
TITANIUM DIOXIDE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In vivo	Not mutagenic
2,6-DI-TERT-BUTYL-P-CRESOL	In Vitro	Not mutagenic
2,6-DI-TERT-BUTYL-P-CRESOL	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED SILICA containing respirable fraction 1-<10%	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
DIATOMACEOUS EARTH	Inhalation	Human and animal	Carcinogenic
TITANIUM DIOXIDE	Ingestion	Multiple animal species	Not carcinogenic
TITANIUM DIOXIDE	Inhalation	Rat	Carcinogenic
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA containing respirable fraction 1-<10%	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA containing respirable fraction 1-<10%	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED SILICA containing respirable fraction 1-<10%	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	Not classified for development	Rat	NOAEL 100	2 generation

				mg/kg/day	
--	--	--	--	-----------	--

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA containing respirable fraction 1-<10%	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
DIATOMACEOUS EARTH	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
DIATOMACEOUS EARTH	Ingestion	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 3,738 mg/kg/day	90 days
TITANIUM DIOXIDE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
TITANIUM DIOXIDE	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-DI-TERT-BUTYL-P-CRESOL	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste

incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Skin Corrosion or Irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 37-9021-9

Issue Date: 09/17/18

Version Number: 2.00

Supersedes Date: 06/20/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES

NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com