

3M General Offices 3M Center St. Paul, MN 55144-1000 1-800-364-3577 or (651) 737-6501 (24 hours)

Safety Data Sheet

2020-10-20 13:04:55.92

Purchase Order #:818Customer Number:009

818654,819157,819353 0096029960

MSDS COORDINATOR DENTAL HEALTH PRODUCTS INC 2614 N SUGAR BUSH RD NEW FRANKEN, WI 54229-9346 USA

Dear MSDS COORDINATOR

Enclosed is the Safety Data Sheet (SDS)* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at www.3m.com/MSDSSearch.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at emsdsadmin@mmm.com

*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 PRODUCT NAME:
 3M™ ESPE™ IMPRINT™ 4 PRELIMINARY PENTA™ Refill

 MANUFACTURER:
 3M

 DIVISION:
 3M ESPE Dental Products

 ADDRESS:
 3M Center, St. Paul, MN 55144-1000, USA

 Telephone:
 1-888-3M HELPS (1-888-364-3577)

 EMERGENCY PHONE:
 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date:03/04/14Supercedes Date:Initial Issue

Document Group: 33-1465-5

ID Number(s):

70-2011-4180-4

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

33-0041-5, 33-0045-6

No revision information is available.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.

MATERIAL SAFETY DATA SHEET 3MTM ESPETM IMPRINTTM 4 PRELIMINARY PENTATM Refill 03/04/14

In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2016,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 33-0041-5 | Version Number: | 4.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 01/20/16 | Supercedes Date: | 10/09/14 |

SECTION 1: Identification

1.1. Product identifier

 $3M^{\mbox{\tiny TM}}$ ESPE $^{\mbox{\tiny TM}}$ IMPRINT $^{\mbox{\tiny TM}}$ 4 PRELIMINARY PENTA $^{\mbox{\tiny TM}}$ Base

Product Identification Numbers LE-F100-1515-6

1.2. Recommended use and restrictions on use

Recommended use Dental Product, Impression Material Restrictions on use For use only by dental professionals.

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Oral Care Solutions Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements Signal word Not applicable.

Symbols Not applicable.

Pictograms

Not applicable.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt | |
|--|------------|---------|--|
| Quartz (14808-60-7), surface modified with | None | 30 - 60 | |
| silsesquioxanes, methyl, ethoxy-terminated (CAS | | | |
| 104780-78-1), bulk material | | | |
| POLY(DIMETHYLSILOXANE) | 63148-62-9 | 10 - 30 | |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | 68855-54-9 | 1 - 20 | |
| VINYL-POLYDIMETHYL SILOXANE | 68083-19-2 | 10 - 20 | |
| DIMETHYL METHYL HYDROGEN SILICONE | 68037-59-2 | 1 - 10 | |
| FLUID | | | |
| SILANE TREATED SILICA | 67762-90-7 | 1 - 10 | |
| Titanium Dioxide | 68917-18-0 | 1.0 | |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Condition

Carbon monoxide Carbon dioxide Irritant Vapors or Gases During Combustion During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------|------------|--------|--------------------------------|---------------------|
| SILANE TREATED SILICA | 67762-90-7 | CMRG | CEIL:5 mg/m3 | |
| SILICA, AMORPHOUS | 67762-90-7 | OSHA | TWA concentration:0.8 | |
| | | | mg/m3;TWA:20 millions of | |
| | | | particles/cu. ft. | |
| Cristobalite | 68855-54-9 | ACGIH | TWA(respirable | A2: Suspected human |
| | | | fraction):0.025 mg/m3 | carcin. |
| Cristobalite | 68855-54-9 | OSHA | TWA concentration(as total | |
| | | | dust):0.15 mg/m3;TWA | |
| | | | concentration(respirable):0.05 | |
| | | | mg/m3(1.2 millions of | |
| | | | particles/cu. ft.) | |
| SILICA, AMORPHOUS | 68855-54-9 | OSHA | TWA concentration:0.8 | |
| | | | mg/m3;TWA:20 millions of | |
| | | | particles/cu. ft. | |

ACGIH : American Conference of Governmental Industrial Hygienists AIHA : American Industrial Hygiene Association CMRG : Chemical Manufacturer's Recommended Guidelines OSHA : United States Department of Labor - Occupational Safety and Health Administration TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Odor, Color, Grade:SOdor threshold1pH1Melting point1Boiling Point1 | Paste Smell of mint, pink colored paste No Data Available Not Applicable Not Applicable Flash point > 93 °C (200 °F) |
|--|---|
| Odor thresholdIpHIMelting pointIBoiling PointI | No Data Available Not Applicable Not Applicable Not Applicable |
| pHIMelting pointIBoiling PointI | Not Applicable Not Applicable Not Applicable |
| Melting pointIBoiling PointI | Not Applicable Not Applicable |
| Boiling Point | Not Applicable |
| | |
| Flash Point | Elash point > 93 °C (200 °E) |
| | 1 mon point > > > > < (200 1) |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapor Pressure | No Data Available |
| Vapor Density | No Data Available |
| Density | 1.5 g/cm3 - 1.7 g/cm3 |
| Specific Gravity | 1.5 - 1.7 [<i>Ref Std:</i> WATER=1] |
| Solubility in Water | Negligible |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | Not Applicable |
| Decomposition temperature | No Data Available |
| Viscosity | No Data Available |
| Volatile Organic Compounds | Not Applicable |
| Percent volatile | Not Applicable |
| VOC Less H2O & Exempt Solvents | Not Applicable |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat

10.5. Incompatible materials Amines Strong acids Strong bases Strong oxidizing agents

10.6. Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|-----------------------|------------|--------------------------------|---|
| SILICA, CRYS AIRRESP | 68855-54-9 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| SILICA, CRYS AIRRESP | 68855-54-9 | Known human carcinogen | National Toxicology Program Carcinogens |
| Generic: Cristobalite | 68855-54-9 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Titanium Dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|---------------------------------------|-----------------------------------|---|
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| POLY(DIMETHYLSILOXANE) | Dermal | Rabbit | LD50 > 19,400 mg/kg |
| POLY(DIMETHYLSILOXANE) | Ingestion | Rat | LD50 > 17,000 mg/kg |
| VINYL-POLYDIMETHYL SILOXANE | Dermal | Rabbit | LD50 > 15,440 mg/kg |
| VINYL-POLYDIMETHYL SILOXANE | Ingestion | Rat | LD50 > 15,440 mg/kg |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Dermal | Professio nal judgeme nt | LD50 estimated to be > 5,000 mg/kg |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 2.7 mg/l |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Ingestion | Rat | LD50 > 2,000 mg/kg |
| SILANE TREATED SILICA | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| SILANE TREATED SILICA | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| SILANE TREATED SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Titanium Dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium Dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|----------|---------------------------|
| | | |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy- | | No significant irritation |
| terminated (CAS 104780-78-1), bulk material | | |
| POLY(DIMETHYLSILOXANE) | Rabbit | No significant irritation |
| VINYL-POLYDIMETHYL SILOXANE | Rabbit | No significant irritation |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | In vitro | No significant irritation |

| | data | |
|-----------------------|--------|---------------------------|
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| Titanium Dioxide | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| | | |
| POLY(DIMETHYLSILOXANE) | Rabbit | No significant irritation |
| VINYL-POLYDIMETHYL SILOXANE | Rabbit | Mild irritant |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Rabbit | Mild irritant |
| SILANE TREATED SILICA | Rabbit | No significant irritation |
| Titanium Dioxide | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|--|---------------|-----------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Mouse | Not sensitizing |
| SILANE TREATED SILICA | Human | Not sensitizing |
| | and animal | |
| | | NT |
| Titanium Dioxide | Human | Not sensitizing |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy- terminated (CAS 104780-78-1), bulk material | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy- terminated (CAS 104780-78-1), bulk material | In vivo | Some positive data exist, but the data are not sufficient for classification |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| SILANE TREATED SILICA | In Vitro | Not mutagenic |
| Titanium Dioxide | In Vitro | Not mutagenic |
| Titanium Dioxide | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|------------|----------|--|
| Quartz (14808-60-7), surface modified with silsesquioxanes, | Inhalation | Human | Carcinogenic |
| methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | | and | |
| | | animal | |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Inhalation | Human | Carcinogenic |
| | | and | |
| | | animal | |
| SILANE TREATED SILICA | Not | Mouse | Some positive data exist, but the data are not |
| | Specified | | sufficient for classification |
| Titanium Dioxide | Ingestion | Multiple | Not carcinogenic |
| | | animal | |
| | | species | |
| Titanium Dioxide | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-----------------------|-----------|----------------------------------|---------|------------------------|----------------------|
| SILANE TREATED SILICA | Ingestion | Not toxic to female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| SILANE TREATED SILICA | Ingestion | Not toxic to male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |

3MTM ESPETM IMPRINTTM 4 PRELIMINARY PENTATM Base 01/20/16

| SILANE TREATED SILICA | Ingestion | Not toxic to development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |
|-----------------------|-----------|--------------------------|-----|--------------------------|-----------------------------|
|-----------------------|-----------|--------------------------|-----|--------------------------|-----------------------------|

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|--|--|---------|-----------------------------|--------------------------|
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Ingestion | hematopoietic system eyes kidney and/or bladder | All data are negative | Rat | NOAEL 3,738 mg/kg/day | 90 days |
| SILANE TREATED SILICA | Inhalation | respiratory system silicosis | All data are negative | Human | NOAEL Not available | occupational exposure |
| Titanium Dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium Dioxide | Inhalation | pulmonary fibrosis | All data are negative | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 33-0041-5 | Version Number: | 4.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 01/20/16 | Supercedes Date: | 10/09/14 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable

for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2016,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 33-0045-6 | Version Number: | 2.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 02/25/16 | Supercedes Date: | 02/17/14 |

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM IMPRINTTM 4 PRELIMINARY PENTATM Catalyst

Product Identification Numbers LE-F100-1515-8

1.2. Recommended use and restrictions on use

Recommended use Dental Product, Impression Material Restrictions on use For use only by dental professionals.

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Oral Care Solutions Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements Signal word Not applicable.

Symbols Not applicable.

Pictograms

Not applicable.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|-------------------------------------|------------|---------|
| SODIUM ALUMINUM SILICATE | 37244-96-5 | 60 - 70 |
| VINYL-POLYDIMETHYLSILOXANE | 68083-19-2 | 20 - 30 |
| POLY(DIMETHYLSILOXANE) | 63148-62-9 | 1 - 15 |
| DIMETHYL SILOXANE, REACTION PRODUCT | 67762-90-7 | 1 - 10 |
| WITH SILICA | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| Substance | <u>Condition</u> |
|--------------------------|-------------------|
| Formaldehyde | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Irritant Vapors or Gases | During Combustion |

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Vacuum or sweep up. WARNING ! A motor could be an ignition source and cause flammable gases or vapors or dust in the spill area to burn or explode. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|------------|--------|--|----------------------------|
| SODIUM ALUMINUM SILICATE | 37244-96-5 | CMRG | TWA(respirable):5 mg/m3 | |
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | 67762-90-7 | CMRG | CEIL:5 mg/m3 | |
| SILICA, AMORPHOUS | 67762-90-7 | OSHA | TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft. | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

No chemical protective gloves are required. See Section 7.1 for additional information on skin protection.

Respiratory protection None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| General Physical Form: | Solid |
|---|---|
| Specific Physical Form: | Paste |
| Odor, Color, Grade: | slight characteristic odor; white colored paste |
| Odor threshold | No Data Available |
| рН | No Data Available |
| Melting point | Not Applicable |
| Boiling Point | Not Applicable |
| Flash Point | No flash point |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | No Data Available |
| Vapor Density | No Data Available |
| Density | 1.5 g/cm3 - 1.7 g/cm3 |
| Specific Gravity | 1.5 - 1.7 [<i>Ref Std:</i> WATER=1] |
| Solubility in Water | Negligible |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity | No Data Available |
| Volatile Organic Compounds | Not Applicable |
| Percent volatile | Not Applicable |
| VOC Less H2O & Exempt Solvents | Not Applicable |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products

Substance None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No known health effects.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------------|-----------|---------|---|
| Overall product | Ingestion | | No data available; calculated ATE 2,000 - 5,000 |
| | | | mg/kg |
| SODIUM ALUMINUM SILICATE | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| SODIUM ALUMINUM SILICATE | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |

| VINYL-POLYDIMETHYLSILOXANE | Dermal | Rabbit | LD50 > 15,440 mg/kg |
|---|-------------|--------|---------------------|
| VINYL-POLYDIMETHYLSILOXANE | Ingestion | Rat | LD50 > 15,440 mg/kg |
| POLY(DIMETHYLSILOXANE) | Dermal | Rabbit | LD50 > 19,400 mg/kg |
| POLY(DIMETHYLSILOXANE) | Ingestion | Rat | LD50 > 17,000 mg/kg |
| DIMETHYL SILOXANE, REACTION PRODUCT WITH | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| SILICA | | | |
| DIMETHYL SILOXANE, REACTION PRODUCT WITH | Inhalation- | Rat | LC50 > 0.691 mg/l |
| SILICA | Dust/Mist | | |
| | (4 hours) | | |
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|-----------------------------------|---------------------------|
| SODIUM ALUMINUM SILICATE | Professio nal judgeme nt | No significant irritation |
| VINYL-POLYDIMETHYLSILOXANE | Rabbit | No significant irritation |
| POLY(DIMETHYLSILOXANE) | Rabbit | No significant irritation |
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|-----------|---------------------------|
| | | |
| SODIUM ALUMINUM SILICATE | Professio | Mild irritant |
| | nal | |
| | judgeme | |
| | nt | |
| VINYL-POLYDIMETHYLSILOXANE | Rabbit | Mild irritant |
| POLY(DIMETHYLSILOXANE) | Rabbit | No significant irritation |
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---|---------|-----------------|
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Human | Not sensitizing |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|---------------|
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|-----------|---------|--|
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Not | Mouse | Some positive data exist, but the data are not |
| | Specified | | sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--|-----------|----------------------------------|---------|------------------------|----------------------|
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Ingestion | Not toxic to female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| DIMETHYL SILOXANE, REACTION | Ingestion | Not toxic to male reproduction | Rat | NOAEL 497 | 1 generation |

| PRODUCT WITH SILICA | | | | mg/kg/day | |
|--|-----------|--------------------------|-----|--------------------------|-----------------------------|
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Ingestion | Not toxic to development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|-----------------------------------|-----------------------|---------|------------------------|--------------------------|
| DIMETHYL SILOXANE, REACTION PRODUCT WITH SILICA | Inhalation | respiratory system silicosis | All data are negative | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 33-0045-6 | Version Number: | 2.00 |
|------------------------|-----------|------------------|----------|
| Issue Date: | 02/25/16 | Supercedes Date: | 02/17/14 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com