

Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· Product identifier

Trade name: <u>Spraynet</u>
Article number: 1600036

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the preparation:

For industrial use only

Cleaner for dental instruments

Lubricant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer / Supplier:

Bien-Air Dental S.A.

Länggasse 60

CH-2504 Biel/Bienne

Switzerland

Tel.: int. +41 (0)32 344 64 64

office@bienair.com

· Further information obtainable from:

Product Safety Department E-mail: reach@blaser.com

· 1.4 Emergency telephone number:

Toxicological information Switzerland:

24-h-Emergency number: 145 (from abroad: +41 44 251 51 51)

Information: +41 44 251 66 66

For advice on chemical emergencies, spillages, fires or exposures: +44 1235 239670 (24h/7d)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture:
- Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear eye protection / face protection.
P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

(Contd. on page 2)



Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 1)

- · 2.3 Other hazards None
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture: consisting of the following components.

Active substance with propellant

· Declarable, or hazardous components: CAS-no. CAS: 64-17-5 ethanol >40-<70% EINECS: 200-578-6 Flam. Liq. 2, H225; Eye Irrit. 2, H319 Reg.nr.: 01-2119457610-43-0000 CAS: 106-97-8 butane >10-<30% EINECS: 203-448-7 Flam. Gas 1, H220; Press. Gas C, H280 CAS: 74-98-6 propane >10-<30% EINECS: 200-827-9 Flam. Gas 1, H220; Press. Gas C, H280 CAS: 67-63-0 isopropanol >1-<5% EINECS: 200-661-7 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 Reg.nr.: 01-2119457558-25-0000

· Additional information:

Not mentioned CAS-, EINECS- or registration numbers are to be regarded as Proprietary/Confidential.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

- · 4.2 Most important symptoms and effects, both acute and delayed Nausea / vomiting
- · 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- \cdot Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)



Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 2)

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials. Observe the general safety regulations when handling chemicals.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Optimal storage temperature between -20 °C and +40 °C.

Duration of storage: In original container, at least 6 years.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values at the workplace:		
64-17-5 ethanol		
AGW (Germany)	Long-term value: 960 mg/m³, 500 ppm 2(II);DFG, Y	
WEL (Great Britain)	Long-term value: 1920 mg/m³, 1000 ppm	
74-98-6 propane		
AGW (Germany)	Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG	
106-97-8 butane		
AGW (Germany)	Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG	
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	

Contd. on page



Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 3)

67-63-0 isopropanol

AGW (Germany) Long-term value: 500 mg/m³, 200 ppm

2(II); DFG, Y

WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

· Ingredients with biological limit values:

67-63-0 isopropanol

BGW (Germany) 25 mg/l

Untersuchungsmaterial: Vollblut

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: Aceton

25 mg/l

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: Aceton

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the resultant standard EN 374.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

The break through, among others, depending on material density and the type of glove and therefore must be determined in each individual case.

Gloves must be inspected prior to use. Replace when worn!

Impervious gloves: nitrile rubber, minimum thickness of 0.3 mm.

· Penetration time of glove material

The exact breaktrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Eye protector with side protection (framed eyeglasses) EN 166.
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Colourless

(Contd. on page 5)



Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 4) Odour: **Peppermint Odour threshold:** Not determined. · pH-value: Not applicable. · Change in condition: Melting point/freezing point: Not applicable Initial boiling point and boiling range: Active substance: >78 °C (DIN 51751 / ASTM D86) Not applicable, as aerosol. **Drip point:** Not applicable Pour point: Active substance: < 0 °C (ISO 3016 / ASTM D97) · Flash point: Active substance: 12 °C. (ISO 2592 / ASTM D92) Not applicable, as aerosol. · Flammability (solid, gas): Extremely flammable liquefied gas. · Ignition temperature: Active substance: 365 °C (DIN 51794 / ASTM E659) · Decomposition temperature: Not determined. · Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Explosion limits (@1013 mbar): Lower: 1.5 Vol % Upper: 15.0 Vol % Oxidising properties Not applicable. · Density: Active substance: 0.79 g/cm³ @ 20 °C (DIN 51757 / ASTM D1217) · Vapour density Not applicable. · Evaporation rate Not applicable. · Solubility in / Miscibility with water: Partly miscible. · Partition coefficient: n-octanol/water: Not determined. · Viscosity: **Kinematic:** Active substance: 1,2 mm²/s @ 40 °C (ISO 3104 / ASTM D445) 95.82 % VOC (CH): · 9.2 Other information: safety relevant data, which has to be considered as product specifications.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity None known if used as directed.
- 10.2 Chemical stability Stable under recommended storage conditions.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:
- > 2000 < 5000 mg / kg (oral, rat)
- > 5,100 mg/m³ 4h (inhalation, rat)

(Contd. on page 6)



Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 5)

*	pure	substance
---	------	-----------

64-17-5 et		
Oral	LD50	7060 mg/kg (rat)
Inhalative	LD50	20000 mg/L (rat)

106-97-8 butane

Inhalative LD50 658 mg/L (rat)

67-63-0 isopropanol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LD50	30 mg/L (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Do not allow product to reach ground water, water course or sewage system.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- u. • p•u	madio dataloguo
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950

(Contd. on page 7)



Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 6) · 14.2 UN proper shipping name · ADR 1950 AEROSOLS · IMDG **AEROSOLS** ·IATA AEROSOLS, flammable · 14.3 Transport hazard class(es) · ADR · Class 2 5F Gases. · Label 2.1 · IMDG, IATA · Class 2.1 · Label 2.1 Not applicable · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D.S-U · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D 1L · Limited quantities (LQ) · Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity



Printing date 15.02.2017 Version number 10 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 7)

· IATA Dangerous Goods Regulation (DGR): latest edition

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008: CLP/GHS label elements are issued under section 2.
- · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- · CPID-no. (CH): 250579-14
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- · Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57
 This preparation does not contain any SVHC ("Substances of Very High Concern")
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Regulations / approvals / listings:

Information on REACH registration numbers in section 3:

In case of lack of REACH registration numbers on mentioned hazardous substances at the end of 2010, then these numbers will be known and indicated only in section 3 within its tonnage band for registration, after the end of 2013, respectively by the end of 2018, or are exempt from the REACH regulation (e.g. polymers).

All major components comply to the US-FDA rule 21 CFR 178.3570 (Lubricants with incidental food contact), or correspond to the current Pharmacopoeia or food grade requirements.

All contents comply with current pharmacological or food grade standards.

· RoHS:

The product is compliant with European Directives 2015/863/EC, 2011/65/EC, 2002/95/EC, WEEE 2002/96/EC, 2003/11/EC, 2005/53/EC and RoHS.

The following substances ARE NOT contained:

Pentabromodiphenylether, Octabromodiphenylether, polybrominated diphenylether (PDBE) and / or polybrominated biphenyls (PBB), Bis(2-ethylhexyl)phthalate (DEHP), Benzylbutylphthalate (BBP), Dibutylphthalate (DBP), Diisobutylphthalate (DIBP):

lead or it's compounds, cadmium or it's compounds, mercury or it's compounds, chromium Cr6+-compounds.

· TSE/BSE:

This product adheres to the standards of TSE/BSE-free products, according to European Community directives 93/42/ EEC and 2003/32/EC.

Materials and/or synthetically modified materials which are of animal origin from bovine, ovine, goats, cats, dogs, deer, elk and/or mink, are NOT included in this product.

This product is entirely free from latex containing materials.

· Department issuing SDS: Product Stewardship

(Contd. on page 9)



Version number 10 Printing date 15.02.2017 Revision: 15.02.2017

Trade name: Spraynet

(Contd. of page 8)

· Editor's notice:

The above mentioned data correspond to our present state of knowledge and experience. The safety data sheet serves as description of the products in regard to necessary safety measures. The indications have not the meaning of guarantees on properties.

· Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

RoHS: Restriction of Hazardous Substances

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) ISO: International Organisation for Standardisation

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

ATE: Acute Toxicity Estimate

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.

The asterisk (*) on the left side indicate the respective changes from the previous version.