

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

STATMATIC Spray NA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

No information available.

1.3. Details of the supplier of the safety data sheet

| | | |
|---------------|------------------------------|--------------------------|
| Company name: | SciCan Ltd. | |
| Street: | 1440 Don Mills Road | |
| Place: | CDN-M3B 3P9 Toronto, Ontario | |
| Telephone: | +1 416-446-2742 | Telefax: +1 416-446-2725 |
| e-mail: | aceccanese@scican.com | |
| Internet: | www.scican.com | |

1.4. Emergency telephone number: 111 NHS (National Health Service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
 Aerosol: Aerosol 1
 Hazard Statements:
 Extremely flammable aerosol.
 Pressurised container: May burst if heated.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
 The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 2 of 10

Hazardous components

| CAS No | Chemical name | | | Quantity |
|----------|---------------------------------------|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | GHS Classification | | | |
| 75-28-5 | isobutane | | | 25 - < 50 % |
| | 200-857-2 | 601-004-00-0 | 01-2119485395-27 | |
| | Flam. Gas 1, Liquefied gas; H220 H280 | | | |
| 106-97-8 | butane | | | 25 - < 50 % |
| | 203-448-7 | 601-004-00-0 | 01-2119474691-32 | |
| | Flam. Gas 1, Liquefied gas; H220 H280 | | | |
| 74-98-6 | propane | | | 5 - < 10 % |
| | 200-827-9 | 601-003-00-5 | 01-2119486944-21 | |
| | Flam. Gas 1, Liquefied gas; H220 H280 | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO₂). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 3 of 10

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
When using do not eat, drink, smoke, sniff.
Wear personal protection equipment (refer to section 8).
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 4 of 10

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|----------|-----------|-----|-------------------|-----------|---------------|--------|
| 106-97-8 | Butane | 600 | 1450 | | TWA (8 h) | WEL |
| | | 750 | 1810 | | STEL (15 min) | WEL |

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long term exposure: after several previous shifts
- d before next shift

- blood (B)
- Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min
Thickness of the glove material 0,45 mm
DIN EN 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
When exceeding the relevant workplace exposure limits, note the following:
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
Filtering device with filter or ventilator filtering device of type: AX
Observe the wear time limits as specified by the manufacturer.
Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: light yellow
Odour: characteristic

pH-Value (at 20 °C):

Test method
DIN 19268

Changes in the physical state

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 5 of 10

Initial boiling point and boiling range: -40 °C

Flash point: -80 °C

Flammability

Solid: not applicable

Gas: not applicable

Lower explosion limits: 1 vol. %

Upper explosion limits: 11 vol. %

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

 Density (at 20 °C): 0,853 g/cm³ DIN 51757

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

density: Data apply to technical substance.

pressure: ca. 4,1 bar (20°C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

 Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO₂, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 6 of 10

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | |
|----------|----------------------|----------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 75-28-5 | isobutane | | | | |
| | inhalation vapour | LC50 1237 mg/l | Mouse. | | |
| 106-97-8 | butane | | | | |
| | inhalation (4 h) gas | LC50 658 ppm | Rat | GESTIS | |

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information

12.1. Toxicity

According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

Safety Data Sheet

Your Infection Control Specialist™

according to Regulation (EC) No 1907/2006

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 7 of 10

| CAS No | Chemical name | | | | | |
|----------|--------------------------|---------------|-----------|---------|----------------------------|--|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 75-28-5 | isobutane | | | | | |
| | Acute fish toxicity | LC50 mg/l | 91,42 | 96 h | Fish, no other information | United States Environmental Protection A The Ecosar class program has been develo |
| | Acute algae toxicity | ErC50 mg/l | 19,37 | 96 h | Algae | USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00. |
| | Acute crustacea toxicity | EC50 mg/l | 69,43 | 48 h | Daphnia sp. | USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00. |
| 106-97-8 | butane | | | | | |
| | Acute fish toxicity | LC50 mg/l | 49,9 | 96 h | Fish, no other information | United States Environmental Protection A The Ecosar class program has been develo |
| | Acute algae toxicity | ErC50 mg/l | 19,37 | 96 h | Algae | USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00. |
| | Acute crustacea toxicity | EC50 mg/l | 69,43 | 48 h | Daphnia sp. | USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00. |
| 74-98-6 | propane | | | | | |
| | Acute fish toxicity | LC50 mg/l | 49,9 | 96 h | Fish, no other information | United States Environmental Protection A The Ecosar class program has been develo |
| | Acute algae toxicity | ErC50 mg/l | 19,37 | 96 h | Algae | USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00. |
| | Acute crustacea toxicity | EC50 mg/l | 69,43 | 48 h | Daphnia sp. | USEPA OPPT Risk Assessment Division (200) Calculation using ECOSAR Program v1.00. |

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|---------------|---------|
| 75-28-5 | isobutane | 1,09 |
| 106-97-8 | butane | 1,09 |
| 74-98-6 | propane | 1,09 |

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

No special environmental measures are necessary.

Safety Data Sheet

Your Infection Control Specialist™

according to Regulation (EC) No 1907/2006

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 8 of 10

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)

| | |
|--|-----------------|
| 14.1. UN number: | UN 1950 |
| 14.2. UN proper shipping name: | AEROSOLS |
| 14.3. Transport hazard class(es): | 2 |
| 14.4. Packing group: | - |
| Hazard label: | 2.1 |
| Classification code: | 5F |
| Special Provisions: | 190 327 344 625 |
| Limited quantity: | 1 L |
| Excepted quantity: | E0 |
| Transport category: | 2 |
| Tunnel restriction code: | D |

Inland waterways transport (ADN)

| | |
|--|-----------------|
| 14.1. UN number: | UN 1950 |
| 14.2. UN proper shipping name: | AEROSOLS |
| 14.3. Transport hazard class(es): | 2 |
| 14.4. Packing group: | - |
| Hazard label: | 2.1 |
| Classification code: | 5F |
| Special Provisions: | 190 327 344 625 |
| Limited quantity: | 1 L |
| Excepted quantity: | E0 |

Marine transport (IMDG)

| | |
|--|----------|
| 14.1. UN number: | UN 1950 |
| 14.2. UN proper shipping name: | AEROSOLS |
| 14.3. Transport hazard class(es): | 2.1 |
| 14.4. Packing group: | - |

Safety Data Sheet

Your Infection Control Specialist™

according to Regulation (EC) No 1907/2006

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 9 of 10

| | |
|---------------------|---------------------------------|
| Hazard label: | 2.1 |
| Marine pollutant: | no |
| Special Provisions: | 63, 190, 277, 327, 344, 381,959 |
| Limited quantity: | 1000 mL |
| Excepted quantity: | E0 |
| EmS: | F-D, S-U |

Air transport (ICAO-TI/IATA-DGR)

| | |
|--|---------------------|
| 14.1. UN number: | UN 1950 |
| 14.2. UN proper shipping name: | AEROSOLS, flammable |
| 14.3. Transport hazard class(es): | 2.1 |
| 14.4. Packing group: | - |
| Hazard label: | 2.1 |
| Special Provisions: | A145 A167 A802 |
| Limited quantity Passenger: | 30 kg G |
| Passenger LQ: | Y203 |
| Excepted quantity: | E0 |
| IATA-packing instructions - Passenger: | 203 |
| IATA-max. quantity - Passenger: | 75 kg |
| IATA-packing instructions - Cargo: | 203 |
| IATA-max. quantity - Cargo: | 150 kg |

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; butane

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional information

 Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
 Aerosol directive (75/324/EEC)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 2,3,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

Safety Data Sheet

Your Infection Control Specialist™

according to Regulation (EC) No 1907/2006

STATMATIC Spray NA

Revision date: 29.05.2019

Product code: 11AA5420934A0500CA

Page 10 of 10

IATA: International Air Transport Association
 IMDG: International Maritime Code for Dangerous Goods
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level
 WEL (UK): Workplace Exposure Limits
 TWA (EC): Time-Weighted Average
 ATE: Acute Toxicity Estimate
 STEL (EC) Short Term Exposure Limit
 LC50: Lethal Concentration
 EC50: half maximal Effective Concentration
 ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

| Classification | Classification procedure |
|----------------------|--------------------------|
| Aerosol 1; H222-H229 | On basis of test data |

Relevant H and EUH statements (number and full text)

| | |
|------|---|
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H280 | Contains gas under pressure; may explode if heated. |

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:
 Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)