Date Prepared : 10/06/2008 MSDS No : BS1009 Date Revised : 10/28/2015 Revision No : 8

Porcelain Conditioner

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Porcelain Conditioner GENERAL USE: Preparation of glazed dental porcelain for bonding. PRODUCT DESCRIPTION: 6851M6XU PRODUCT CODE: OT-PO CHEMICAL FAMILY: Isopropanol GENERIC NAME: Isopropanol

MANUFACTURER

Ortho Technology, Inc. 17401 Commerce Park Boulevard Tampa, FL 33647 **Emergency Phone:** 1-800-999-3161 **E-Mail:** Ijohnson@orthotechnology.com

24 HR. EMERGENCY TELEPHONE NUMBERS

For Chemical Emergency Spill Leak or Fire Exposure or Accident Call CHEMTREC Day or Night Domestic North America 1-800-424-9300 International, Call +1 703-527-3887 (collect calls accepted)

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Physical:

Flammable Liquids, Category 1

GHS LABEL



HAZARD STATEMENTS

H226: Flammable liquid and vapour. H320: Causes eye irritation.

PRECAUTIONARY STATEMENT(S)

Response:

P305: IF IN EYES:.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear colorless liquid with rubbing alcohol odor

IMMEDIATE CONCERNS: Eye irritant, flammable.

POTENTIAL HEALTH EFFECTS

EYES: Vapor and mist may cause irritation, pain, eye burns, or permanent eye damage.

SKIN: Prolonged or repeated skin contact may cause drying, cracking or irritation.

INGESTION: May be harmful if ingested in sufficient quantities. May cause dizziness, drowsiness, vomiting, nausea, lack of coordination.

INHALATION: High vapor or mist concentrations may cause drowsiness and irritation of the respiratory tract.

Date Prepared : 10/06/2008 MSDS No : BS1009 Date Revised : 10/28/2015 Revision No : 8

Porcelain Conditioner

ROUTES OF ENTRY: Inhalation, Ingestion, and Skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
Isopropanol	> 80	67-63-0
Silane	< 20	2530-85-0

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water for at least fifteen minutes. Seek medical attention by an Ophtalmologist.

SKIN: Wash off with soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. If irritation persists consult a physician.

INGESTION: Seek medical advice immediately.

INHALATION: Remove from exposure. Give artificial respiration is not breathing.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Chemical Foam, Carbon Dioxide, or Dry Chemical, water spray.

EXPLOSION HAZARDS: None

FIRE FIGHTING EQUIPMENT: Wear self-contained breathing apparatus and protective clothing.

FIRE EXPLOSION: Flammable liquid and vapor. Vapors may travel to source of ignition and flashback. Vapors may settle in low or confined spaces.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: METHOD FOR CLEANING UP: Contain spilled liquid with vermicullite or sand and place waste in container. Prevent runoff from entering drains, sewers and streams.

LARGE SPILL: METHOD FOR CLEANING UP: Contain spilled liquid with vermicullite or sand and place waste in container. Prevent runoff from entering drains, sewers ans streams.

GENERAL PROCEDURES: Do not dump the spilled material in sewer.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes, skin, and clothing. Use adequate ventilation. Wash thoroughly after handling.

STORAGE: Store at ambient room temperature, in a dry well-ventilated place. Keep away from sources of heat amd ignition. Do not freeze.

STORAGE TEMPERATURE: Ambient room temperature.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Use with adequate ventilation. If product is used in confined space or at above ambient temperatures use of local exhaust ventilation is recommended.

PERSONAL PROTECTIVE EQUIPMENT

Date Prepared : 10/06/2008 MSDS No : BS1009 Date Revised : 10/28/2015 Revision No : 8

Porcelain Conditioner

EYES AND FACE: Safety glasses or Goggles with side shields recommended.

SKIN: Clothing should be sufficient to minimize physical contact and avoid exposure.

RESPIRATORY: Avoid prolonged breathing of vapors. If airborne particles are not controlled below exposure limits, repirator must be worn. Respirator type : Mist, organic vapor.

PROTECTIVE CLOTHING: Wear lab coat

WORK HYGIENIC PRACTICES: Normal safe practices. Use only in a highly professional manner.

OTHER USE PRECAUTIONS: For operations where prolonged or repeated contact may occur use chemically impervious Gloves.

COMMENTS: Limits : TWA: 400 PPM; STEL 500 PPM.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid ODOR: Rubbing alcohol odor APPEARANCE: Clear colorless liquid. COLOR: Colorless FLASHPOINT AND METHOD: 13°C Closed Cup VAPOR PRESSURE: 33 mmHg at 20°C BOILING POINT: 82°C SOLUBILITY IN WATER: Soluble EVAPORATION RATE: (Butyl acetate = 1) 1.8 SPECIFIC GRAVITY: (H2O = 1) 0.8

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur.
STABILITY: Stable in normal storage conditions.
CONDITIONS TO AVOID: Temperatures aver 27 C and contamination.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide and carbon monooxide.
INCOMPATIBLE MATERIALS: Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: May cause irritation, pain, eye burns, or permanent eye damage. **SKIN EFFECTS:** Prolonged or repeated skin contact may cause drying, cracking or irritation. **GENERAL COMMENTS:** No known carcinogens present.

12. ECOLOGICAL INFORMATION

GENERAL COMMENTS: Avoid releasing the product into environment.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Incinerate or dispose according to local, state, and federal regulations.

Date Prepared : 10/06/2008 MSDS No : BS1009 Date Revised : 10/28/2015 Revision No : 8

Porcelain Conditioner

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION) PROPER SHIPPING NAME: Isopropanol PRIMARY HAZARD CLASS/DIVISION: 3 UN/NA NUMBER: UN1219 PACKING GROUP: II NAERG: 129 LABEL: Flammable Liquid AIR (ICAO/IATA) SHIPPING NAME: Isopropanol UN/NA NUMBER: UN1219 PRIMARY HAZARD CLASS/DIVISION: 3 PACKING GROUP: II ERG: 129 LABEL: Flammable Liquid

15. REGULATORY INFORMATION

16. OTHER INFORMATION

REASON FOR ISSUE: New MSDS Format

APPROVED BY: J.Hutchins TITLE: QA/RA Director

PREPARED BY: T.Swan Date Revised: 10/28/2015

INFORMATION CONTACT: 1-800-999-3161

REVISION SUMMARY: This MSDS replaces the 03/19/2014 MSDS. Revised: Section 1: REASON FOR ISSUE.

ADDITIONAL MSDS INFORMATION: Safety Phrases : S16 Keep away from sources of ignition

S23 Do not breathe fumes

S24/25 Avoid contact with skin and eyes

S26/28 If contact with eyes and skin, wash with plenty of water

GENERAL STATEMENTS: CAUTION: PRODUCT FOR PROFESSIONAL USE ONLY

MANUFACTURER DISCLAIMER: The above information is based on presently available data and to the best of our knowledge for handling the product under normal conditions. Any use of this product in any way not indicated on this document or using it together with any other process/procedure will be exclusively under the user's responsibility.