



## Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	26-9856-1	<b>Version Number:</b>	3.05
<b>Issue Date:</b>	01/08/18	<b>Supersedes Date:</b>	12/29/17

### SECTION 1: Identification

#### 1.1. Product identifier

12149/ 12150/ 12151/ 12154/ 12159/ 12160 3M™ ESPE™ VANISH™ 5% NaF WHITE VARNISH WITH TCP

#### Product Identification Numbers

LE-F100-1935-7, 70-2010-5739-8, 70-2010-5740-6, 70-2010-5742-2, 70-2010-5744-8, 70-2010-5747-1, 70-2010-5749-7, 70-2010-5750-5, 70-2010-5751-3, 70-2010-5752-1, 70-2010-8812-0, 70-2010-8813-8, 70-2010-8814-6, 70-2010-8815-3, 70-2010-8816-1, 70-2010-8817-9, 70-2010-8818-7, 70-2010-8819-5, 70-2010-8820-3, 70-2010-8821-1, 70-2010-8822-9, 70-2010-8823-7, 70-2010-8824-5, 70-2010-8825-2, 70-2010-8849-2, 70-2010-8850-0, 70-2010-8851-8, 70-2014-0443-4, 70-2014-0550-6, 70-2014-0551-4, 70-2014-0552-2, 70-2014-0565-4, 70-2014-0566-2, 70-2014-0567-0

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Dental Product, Fluoride Varnish

##### Restrictions on use

For use only by dental professionals

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Oral Care Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Flammable Liquid: Category 3.

Aspiration Hazard: Category 1.

Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Flame | Exclamation mark | Health Hazard |

### Pictograms



### Hazard Statements

Flammable liquid and vapor.

May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure:  
musculoskeletal system |  
nervous system |

### Precautionary Statements

#### Prevention:

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Use only in a well-ventilated area.  
Wear protective gloves and eye/face protection.  
Do not eat, drink or smoke when using this product.  
Wash thoroughly after handling.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
Do NOT induce vomiting.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
IF exposed or concerned: Get medical advice/attention.  
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### Storage:

Store in a well-ventilated place. Keep cool.  
Keep container tightly closed.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
PENTAERYTHRITOL GLYCEROL ESTER OF COLOPHONY RESIN	Trade Secret*	30 - 75 Trade Secret *
n-HEXANE	110-54-3	10 - 15 Trade Secret *
ETHYL ALCOHOL	64-17-5	1 - 15 Trade Secret *
SODIUM FLUORIDE	7681-49-4	1 - 5 Trade Secret *
FLAVOR ENHANCER	Trade Secret*	1 - 5 Trade Secret *
THICKENER	Trade Secret*	1 - 5 Trade Secret *
FOOD GRADE FLAVOR	None	1 - 5 Trade Secret *
MODIFIED TRICALCIUM PHOSPHATE	None	< 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

No need for first aid is anticipated.

**If Swallowed:**

Do not induce vomiting. Get immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide  
Carbon dioxide

**Condition**

During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid prolonged or repeated skin contact. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
n-HEXANE	110-54-3	OSHA	TWA:1800 mg/m3(500 ppm)	
n-HEXANE	110-54-3	ACGIH	TWA:50 ppm	SKIN
ETHYL ALCOHOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	
ETHYL ALCOHOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.
THICKENER	Trade	OSHA	TWA concentration:0.8	

	Secret		mg/m3;TWA:20 millions of particles/cu. ft.	
--	--------	--	--	--

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

See Section 7.1 for additional information on skin protection.

#### Respiratory protection

None required.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Light yellow liquid with mint, cherry or melon odor
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	68 °C
<b>Flash Point</b>	25 °C [ <i>Test Method:Closed Cup</i> ]
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>Not Applicable</i>
<b>Vapor Density</b>	<i>Not Applicable</i>
<b>Density</b>	0.8 g/ml
<b>Specific Gravity</b>	0.8 [ <i>Ref Std:WATER=1</i> ]
<b>Solubility in Water</b>	Moderate
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>Not Applicable</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<i>No Data Available</i>
<b>Molecular weight</b>	<i>Not Applicable</i>

Volatile Organic Compounds

No Data Available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat

**10.5. Incompatible materials**

Strong oxidizing agents

Strong acids

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Prolonged or repeated exposure may cause target organ effects:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Hard Tissue Effects: Signs/symptoms may include color changes in the teeth and nails; changes in development of bone, teeth or nails; weakening of the bones; and/or hair loss.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Additional Information:**

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion	Rat	LD50 > 2,000 mg/kg
PENTAERYTHRITOL GLYCEROL ESTER OF COLOPHONY RESIN	Dermal		LD50 estimated to be > 5,000 mg/kg
PENTAERYTHRITOL GLYCEROL ESTER OF COLOPHONY RESIN	Ingestion	Rat	LD50 8,400 mg/kg
n-HEXANE	Dermal	Rabbit	LD50 > 2,000 mg/kg
n-HEXANE	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
n-HEXANE	Ingestion	Rat	LD50 > 28,700 mg/kg
ETHYL ALCOHOL	Dermal	Rabbit	LD50 > 15,800 mg/kg
ETHYL ALCOHOL	Inhalation-Vapor (4 hours)	Rat	LC50 124.7 mg/l
ETHYL ALCOHOL	Ingestion	Rat	LD50 17,800 mg/kg

FLAVOR ENHANCER	Dermal		LD50 estimated to be > 5,000 mg/kg
THICKENER	Dermal	Rabbit	LD50 > 5,000 mg/kg
FLAVOR ENHANCER	Ingestion	Rat	LD50 16,500 mg/kg
SODIUM FLUORIDE	Dermal	Rat	LD50 > 2,000 mg/kg
SODIUM FLUORIDE	Inhalation-Dust/Mist	Rat	LC50 1 mg/l
SODIUM FLUORIDE	Ingestion	Rat	LD50 148.5 mg/kg
THICKENER	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
THICKENER	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
n-HEXANE	Human and animal	Mild irritant
ETHYL ALCOHOL	Rabbit	No significant irritation
SODIUM FLUORIDE	official classification	Irritant
THICKENER	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
n-HEXANE	Rabbit	Mild irritant
ETHYL ALCOHOL	Rabbit	Severe irritant
SODIUM FLUORIDE	official classification	Severe irritant
THICKENER	Rabbit	No significant irritation

### Skin Sensitization

Name	Species	Value
n-HEXANE	Human	Not classified
ETHYL ALCOHOL	Human	Not classified
THICKENER	Human and animal	Not classified

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
n-HEXANE	In Vitro	Not mutagenic
n-HEXANE	In vivo	Not mutagenic
ETHYL ALCOHOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHYL ALCOHOL	In vivo	Some positive data exist, but the data are not sufficient for classification
THICKENER	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
n-HEXANE	Dermal	Mouse	Not carcinogenic
n-HEXANE	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification



ETHYL ALCOHOL	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
THICKENER	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
n-HEXANE	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
n-HEXANE	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
n-HEXANE	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
n-HEXANE	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
ETHYL ALCOHOL	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
ETHYL ALCOHOL	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	prematuring & during gestation
THICKENER	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
THICKENER	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
THICKENER	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
n-HEXANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
n-HEXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
n-HEXANE	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
ETHYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
ETHYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ETHYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
SODIUM FLUORIDE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
n-HEXANE	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
n-HEXANE	Inhalation	respiratory system	Some positive data exist, but the	Mouse	LOAEL 1.76	13 weeks

			data are not sufficient for classification		mg/l	
n-HEXANE	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
n-HEXANE	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
n-HEXANE	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
n-HEXANE	Inhalation	auditory system   immune system   eyes	Not classified	Human	NOAEL Not available	occupational exposure
n-HEXANE	Inhalation	heart   skin   endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
n-HEXANE	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
n-HEXANE	Ingestion	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
ETHYL ALCOHOL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ETHYL ALCOHOL	Inhalation	hematopoietic system   immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
ETHYL ALCOHOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
SODIUM FLUORIDE	Inhalation	bone, teeth, nails, and/or hair	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
SODIUM FLUORIDE	Ingestion	bone, teeth, nails, and/or hair	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL 0.33 mg/kg/day	environmental exposure
THICKENER	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure

### Aspiration Hazard

Name	Value
n-HEXANE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

**Health Hazards**

Aspiration Hazard

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
n-HEXANE	110-54-3	Trade Secret 10 - 15
n-HEXANE (Hexane)	110-54-3	10 - 15

**15.2. State Regulations**

Contact 3M for more information.

**California Proposition 65**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
n-HEXANE	110-54-3	Male reproductive toxin

**15.3. Chemical Inventories**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information****NFPA Hazard Classification****Health:** 1 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	26-9856-1	<b>Version Number:</b>	3.05
<b>Issue Date:</b>	01/08/18	<b>Supersedes Date:</b>	12/29/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**