Printing date 05/12/2015

Reviewed on 05/12/2015

1 Identification	
· Product identifier	
· Trade name: Palaseal	
• Relevant identified uses of the substance or mixture and uses	s advised against
No further relevant information available.	2
 Application of the substance / the mixture Auxiliary for man 	ufacture of dental prothesis
 Details of the supplier of the safety data sheet Manufacturer/Supplier: Heraeus Kulzer GmbH Grüner Weg 11, D-63450 Hanau 	Tel.: 0800 4372522
 Information department: Marc Henn Tel. +1 (574) 2995444 / Fax: +1 (574) 2912542 e-mail: marc.henn@kulzer-dental.com Emergency telephone number: Emergency CONTACT (24-Hour-Number) GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or internation 	nal (001) 352 323 3500
* 2 Hazard(s) identification	
 Classification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapor. Repr. 2 H361 Suspected of damaging fertility or the unborn Eye Dam. 1 H318 Causes serious eye damage. Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. 	child.
STOT SE 3 H335 May cause respiratory irritation. • Label elements • GHS label elements The product is classified and labeled according to the Globally • Hazard pictograms	Harmonized System (GHS).
GHS02 GHS05 GHS07 GHS08	
· Signal word Danger	
 Hazard-determining components of labeling: Tris(2-hydroxyethyl)-isocyanurat-triacrylat methyl methacrylate Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxid Bisphenol A Diglycidylether Diacrylat (BADGE-DA) Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. Precautionary statements 	
Keep away from heat/sparks/open flames/hot surfaces No Use explosion-proof electrical/ventilating/lighting/equipment	4 -
	(Contd. on page 2)

Printing date 05/12/2015

Reviewed on 05/12/2015

Trade name: Palaseal

(Contd. of page 1)

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system

• NFPA ratings for USA (scale 0-4)



· HMIS-Ratings (Scale 0-4)



· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

4 First-aid measures

Description of first aid measures

- After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact immediately wash with water and soap and rinse thoroughly.
- After eye contact
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing
- Rinse out mouth and then drink plenty of water.
- If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

• Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

Heraeus Kulzer Mitsui Chemicals Group Page 3/8

Safety Data Sheet acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/12/2015

Trade name: Palaseal

(Contd. of page 2)

- For safety reasons unsuitable extinguishing agents Water.
- Water with full jet.
- · Special hazards arising from the substance or mixture
- Can form explosive gas-air mixtures.
- Formation of toxic gases is possible during heating or in case of fire.
- · Advice for firefighters
 - · Protective equipment: No special measures required.
 - · Additional information -

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up: Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues). Do not flush with water or aqueous cleansing agents
- **Reference to other sections** No dangerous substances are released. See Section 8 for information on personal protection equipment.

7 Handling and storage

- · Precautions for safe handling
- Please observe the additional instructions in the product's instructions for use. Keep receptacles tightly sealed.
 - Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities

· Storage

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep cool, if possible (not above 25 °C).
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

- PEL () 410 mg/m³, 100 ppm
- REL () 410 mg/m³, 100 ppm
- TLV () Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm
 - SEN

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Printing date 05/12/2015

Reviewed on 05/12/2015

Trade name: Palaseal

(Contd. of page 3)

	(Contd. of page 3)
Exposure c	ontrols
	I protective equipment
Gene	ral protective and hygienic measures
Keen	away from foodstuffs, beverages and feed.
Imme	diately remove all soiled and contaminated clothing
Wash	hands before breaks and at the end of work.
	contact with the eyes and skin.
	hing equipment:
Not n	ecessary with efficient local exhaust. If exposition to vapours is possible, use breathing
	ctive mask (filter A).
	ction of hands:
	contact cannot be avoided, protective gloves are recommended to
	possible sensitization.
	love material has to be impermeable and resistant to the product/ the substance/ the
prepa	
	tion of the glove material on consideration of the penetration times, rates of diffusion and
	egradation
	aterial of gloves
Th	e selection of the suitable gloves does not only depend on the material, but also on
	ther marks of quality and varies from manufacturer to manufacturer. As the product is a
	eparation of several substances, the resistance of the glove material can not be
	lculated in advance and has therefore to be checked prior to the application.
	netration time of glove material
	e exact break trough time has to be found out by the manufacturer of the protective
	oves and has to be observed.
	or the permanent contact in work areas without heightened risk of injury (e.g.
	boratory) gloves made of the following material are suitable:
	ear protective gloves based on polyvinyl alcohole.
	or the permanent contact of a maximum of 15 minutes gloves made of the
toi	llowing materials are suitable:
	tyl rubber, BR
FIL	iorocarbon rubber (Viton)
	trile rubber, NBR
	loroprene rubber, CR
	protection: Protective goggles are recommended.
· Body	protection: Light weight protective clothing
Dhusiaal	and abamical properties
Fliysical a	and chemical properties
· Information	on basic physical and chemical properties
	Information
General	

General Information Appearance:		
· Form:	Fluid	
· Color:	Yellow	
· Odor:	Characteristic	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	undetermined 100 °C (212 °F)	
· Flash point:	13 °C (55 °F)	
· Ignition temperature:	430 °C (806 °F)	
· Auto igniting:	Product is not selfigniting.	
		(Contd. on page 5)

Printing date 05/12/2015

Reviewed on 05/12/2015

- UŚA

Trade name: Palaseal

	(Contd. of page
· Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
 Explosion limits: Lower: Upper: 	2.1 Vol % 12.5 Vol %
· Vapor pressure at 20 °C (68	° F) : 47 hPa (35 mm Hg)
· Density at 20 °C (68 °F):	1.060 g/cm³ (8.846 lbs/gal)
Solubility in / Miscibility with Water:	Not miscible or difficult to mix
Viscosity: dynamic at 20 °C (68 °F):	11 mPas
Solvent content: VOC USA	1020.0 g/l / 8.51 lb/gl
Solids content: Other information	32.6 % No further relevant information available.

10 Stability and reactivity

· Possibility of hazardous reactions No dangerous reactions known

- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available. Hazardous decomposition products: none

Additional information:

Product might polymerize after considerable exceeding of recommended storage time or temperature.

11 Toxicological information

· LD/	LC50 valu	es that are relevant for classification:	
80-62-6 m	ethyl met	hacrylate	
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rab)	
Inhalative	LC50/4 h	29.8 mg/l (rat)	
40220-08-	4 Tris(2-h	ydroxyethyl)-isocyanurat-triacrylat	
Oral	LD50	>5000 mg/kg (rat)	
4687-94-9	Bis-Glyci	dylacrylat	
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
52408-84	1 Oligotria	acrylat	
Oral	LD50	>2000 mg/kg (rat)	
· Priı	nary irrita	nt effect:	
		n: Irritant to skin and mucous membranes.	
• •	on the eye	: Strong irritant with the danger of severe eye injury.	
· Ser	sitization	: Sensitization possible through skin contact.	(Contd. on page

Printing date 05/12/2015

Reviewed on 05/12/2015

Trade name: Palaseal

(Contd. of page 5)

3

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
 - · Additional ecological information:
 - · General notes:
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - Recommendation
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1247
· UN proper shipping name	
ADR	1247 METHYL METHACRYLATE MONOME
	STABILIZED, solution
· IMDG, IATA	METHYL METHACRYLATE MONOMER
-	STABILIZED, solution

Reviewed on 05/12/2015

Printing date 05/12/2015

Trade name: Palaseal (Contd. of page 6) · Transport hazard class(es) · DOT · Class 3 Flammable liquids · Label 3 · ADR · Class 3 (F1) Flammable liquids · Label 3 · IMDG, IATA 3 Flammable liquids · Class · Label 3 Packing group DOT, ADR, IMDG, IATA \parallel · Environmental hazards: · Marine pollutant: No Special precautions for user Danger code (Kemler): Warning: Flammable liquids 339 · EMŠ Number: F-E,S-D Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: _ · UN "Model Regulation": UN1247, Methyl methacrylate monomer, stabilized, solution, 3, II

 Safety, heal 	Ith and environmental regulations/legislation specil	fic for the substance or mixture
· SA	RA Section 355 (extremely hazardous substances)	
None of the	ingredients is listed.	
· TSCA	(Toxic Substances Control Act) Medical devices are	e exempted from TSCA.
· Cance	erogenity categories	
· TL	V (Threshold Limit Value established by ACGIH)	
80-62-6 me	thyl methacrylate	A4

(Contd. on page 8)

Printing date 05/12/2015

Reviewed on 05/12/2015

